

se2thesis—A Thesis Class for the Chair of Software Engineering II at the University of Passau, Germany*

Stephan Lukasczyk[†]

Released 2024-02-22

Abstract

One can choose from a wide variety of templates to write a thesis. Many universities provide very rigorous style guides and force their students to obey to those guides, even though they might be questionable from a typography point of view. Other universities do not provide such guides and leave it to their students to choose or come up with a template. The latter is causing very differently-looking theses. To avoid such a situation in the future this bundle combines several L^AT_EX packages and classes for the use at the Chair of Software Engineering II at the University of Passau. We provide, among others, a document class for theses that shall be used by our students. The bundle is designed in a way that one can use the basic components as standalone packages to allow their reuse for other projects.

Contents

I	User Documentation	1
1	Introduction	1
	1.1 Installation	1
	1.2 General Macros	2
2	License	2
3	The se2thesis class	2
	3.1 Load-time options	2
	3.2 The title page	3
	3.3 Type-area settings	4
	3.4 Abstract for the thesis	5
	3.5 Acknowledgements	5
	3.6 Document structuring	5
	3.7 Authorship declaration	6
	3.8 Research Questions and findings summaries	6

*This file describes v3.3.0, last revised 2024-02-22.

[†]E-mail: stephan@dante.de

4	The se2colors package	7
5	The se2fonts package	9
6	The se2packages package	10
6.1	The Recommended Packages	10
6.1.1	Quoting with csquotes	10
6.1.2	Number formatting with siunitx	10
6.1.3	Code Listings	10
6.1.4	Designing Tables	10
6.1.5	Controlling Ligatures, Orphans, and Widows	11
6.1.6	Use microtype for Microtypographic Optimisation	11
6.1.7	Use biblatex for Bibliographic References	11
6.1.8	Use cleveref for Internal References	11
6.2	Loading se2packages	12
6.3	Additional Recommended Packages	13
II	Implementation	15
1	Global helpers	16
2	The se2thesis implementation	16
2.1	Define Variables	17
2.2	Load-time options	18
2.3	Package loading	19
2.4	User macros for the title page	20
2.5	Define logo, paper size, and paper style	21
2.6	The title page	23
2.7	Styling of the sectioning commands	28
2.8	Provide an environment for abstracts	29
2.9	Provide an environment for acknowledgements	29
2.10	Document structuring macros	30
2.11	Declaration of authorship	30
2.12	Research questions and summary boxes	31
3	Translations for se2thesis	32
3.1	English Translations	32
3.2	German Translations	33
4	se2colors implementation	34
4.1	Load-time options	34
4.2	Option handling	34
4.3	Colour definitions	35
5	se2fonts implementation	37
5.1	Load-time options	37
5.2	Option handling	37
5.3	Helper macros	38
5.4	Font loading	38

6	se2packages implementation	40
6.1	Load-time options	40
6.2	Option handling	42
6.3	Package loading	42
	Index	47

Part I

User Documentation

The first part of this file provides the documentation for the user of the `se2thesis` bundle. We provide the implementation in the second part of this document, starting at page 15, for those who are curious.

1 Introduction

The University of Passau does not provide a common thesis template to its students. For theses, written at the Chair of Software Engineering II, many students chose between two templates that were provided by different people from the chair; other students chose from the large variety of templates available from the internet, causing each thesis looking differently.

The author of this package provided a template, which he initially created for his bachelor and master thesis, that was recommended and used by many students. The implementation of that template, however, was very hacky and required some changes over time. This led to the idea of creating a new template from scratch, that shall be used by all our students for their various types of theses, from bachelor to PhD level. The result is the `se2thesis` bundle.

The bundle itself consists of several L^AT_EX classes and packages that also allow reuse of various parts of it. Its main class is the `se2thesis` document class, an extension of the KOMA-Script `scrreprt` document class. The packages `se2colors` and `se2fonts` provide necessary colour and font settings for the `se2thesis` class; the `se2packages` allows to load several recommended packages (see Section 6) with our recommended, predefined settings. They are available as separate packages, however, to allow their reuse for other classes, packages, and projects, as well.

1.1 Installation

The `se2thesis` bundle is available from CTAN¹. It is part of both MiK_TE_X and T_EXLive. You can find its development version from GitHub². The easiest way of installing it is through your T_EX distribution; please check your distribution's documentation on this. Note that it might be necessary to update your T_EX distribution because they might not provide you updates; for example, there is a new version of T_EXLive every year which needs to be installed separately. If you have installed an older version of `se2thesis` consider updating it to the latest version available from CTAN through your distribution.

For manual installation, we recommend to clone the Git repository and run the `l3build` tool that we also use for building the bundle. Running `l3build ctan` builds the source files and compiles the documentation. This creates a folder `build` containing these artefacts; `build/doc` contains the documentation, `build/local` the source files. See the documentation of `l3build` and your T_EX distribution on how to install them manually. Please note that `l3build` also provides a `l3build install` target to install the bundle files to your local `texmf` tree.

The “Island of T_EX” project provides Docker images of T_EXLive³. If you do not want to install/update T_EXLive on your system you might want to consider their latest image, which contains a recent T_EXLive 2023 build. They build their images weekly, thus also recent releases of `se2thesis` will be part of the image soon after their release date.

¹ctan.org/pkg/se2thesis

²github.com/se2p/se2thesis

³islandoftex.gitlab.io/community/projects/docker/

1.2 General Macros

They all have in common one macro, `\IfFormatAtLeastTF`; this macro is part of the latest \LaTeX kernel. However, not all users might have upgraded their \TeX installation to a level using a recently-enough kernel version. Therefore, every class and package of this bundle will conditionally define the following macro:

```
\IfFormatAtLeastTF \IfFormatAtLeastTF {<version>} {<then block>} {<else-block>}
```

Checks whether the used \LaTeX format is at least the one from the given date value. The date needs to be specified either in `YYYY/MM/DD` or in `YYYY-MM-DD` format.

2 License

Permission is granted to copy, distribute, and/or modify this software under the terms of the \LaTeX Project Public License (LPPL), version 1.3c or later (<https://www.latex-project.org/lppl.txt>). The software has the status ‘maintained’.

3 The se2thesis class

The `se2thesis` class is the central component of this bundle. It provides a wide variety of settings, mostly regarding the title page (see Section 3.2) and the type area (see Section 3.3).

We aim to keep the `se2thesis` class relatively small, especially considering packages that we load. Currently, the class itself loads the `se2colors` (see Section 4) and `se2fonts` (see Section 5) packages. The following packages and classes are loaded: `expl3`, `l3keys2e` in case one uses a \LaTeX kernel from before 2022-06-01, `graphicx`, `translations`, `KOMA-Script`, `xcolor`, `ifthen`, as well as `fontspec`, `unicode-math`, and `libertinus-otf` if one uses $\text{Lua}\TeX$; for $\text{pdf}\LaTeX$ we load `fontenc`, `libertinus-type1`, and `AnonymousPro` instead of the latter three. Furthermore, we load `microtype`; when using $\text{Lua}\TeX$, we also load `lua-widow-control` and `selnolig`.

However, we recommend to use a couple of further packages, together with some further options to those package. We describe these settings in Section 6. Please consider looking at this section when starting to write your document.

Before we start with a detailed documentation of the class, we explain one helper macro that can be used to check whether a package has been loaded.

```
\slcd_package_if_loaded_p:n * \slcd_package_if_loaded:nTF {<package name>} {<true code>} {<false code>}
```

```
\slcd_package_if_loaded:nTF * Checks whether a package has been loaded and conditionally executes code.
```

Updated: 2022-09-27

3.1 Load-time options

The `se2thesis` class defines several load-time options, all of them optional, on top of the options provided by the `KOMA-Script` document classes.

```
class class = <choice>
```

Set the base document class. Values are `scrreprt` or `scrbook`. *Note:* you cannot use `scartcl` because it does not provide the required chapter sectioning. Default is `scrbook`.

<code>paper</code>	<code>paper = <choice></code>	Set the paper format. Possible values are a4 or b5. Default is a4.
<code>logfile</code>	<code>logfile = {\<path-to-file>}</code>	Defines the path to the University's logo for the title page.
<code>thesistype</code>	<code>thesistype = <choice></code>	Defines the type of the thesis. Possible values are: <code>bachelor</code> for a bachelor thesis, <code>bachelorproposal</code> for a proposal to a bachelor thesis, <code>master</code> for a master thesis, <code>masterproposal</code> for a proposal to a master thesis, <code>phdproposal</code> for a proposal to a PhD thesis, <code>phd</code> for a PhD thesis in the natural sciences and <code>phdeng</code> for a PhD thesis in engineering.
<code>colormode</code>	<code>colormode = <choice></code>	Select the color scheme used by the automatically loaded <code>se2colors</code> package, see Section 4 for a description.

3.2 The title page

Designing a title package for a thesis can be complicated. There might be some requirements that are not obvious to the user, especially considering the positioning of elements. The University of Passau, for example, requires the logo to be positioned on the top right of a page; theses—especially PhD theses that shall be published through the University's library system—could be rejected from publication by the library until this is fixed.

We thus redeclare the standard `\maketitle` macro from KOMA-Script and customise it to our needs.

<code>\@maketitle</code>	<code>\@maketitle</code>	We override the definition of the <code>\@maketitle</code> macro for our needs. In addition to the macros provided by the KOMA-Script classes for the title-page values (e.g. <code>\author</code> , <code>\title</code>), we provide some further macros that can be used. Setting values to these macros is optional in any case, if they are not set, the corresponding value is not put to the title page.
<code>\version</code>	<code>\version {\<version>}</code>	Specify the version of the document. This can, for example, be a git hash of the current version.
<code>\degreeprogramme</code>	<code>\degreeprogramme {\<programme-name>}</code>	Specify the degree programme the thesis is meant to be accepted in. Possible values are, among others, 'Informatik' if you are writing your thesis in German, or 'Computer Science' if you are writing the thesis in English.
<code>\matrnumber</code>	<code>\matrnumber {\<matriculation-number>}</code>	Specify the matriculation number of the student writing the thesis. This is required for Bachelor and Master theses.

`\supervisor` `\supervisor {<name>}`
`\cosupervisor` `\cosupervisor {<name>}`

Specify the name of your supervisor and co-supervisor. Both people usually are professors.

`\advisor` `\advisor {<name>}`
`\coadvisor` `\coadvisor {<name>}`

Specify the name of your advisor and co-advisor. Both people usually are PhD students or postdocs.

`\department` `\department {<name>}`
`\institute` `\institute [(<short-name>)] {<name>}`

Specify the department and institute. The department is, for example, ‘Faculty of Computer Science and Mathematics’, the institute, for example, ‘Chair of Software Engineering II’. If the `\department` value is not specify, we use ‘Faculty of Computer Science’ as the default value for English theses and ‘Fakultät für Informatik und Mathematik’ as the default value of German theses.

`\external` `\external {<name>}`

Specify the name of an external referee.

`\location` `\location {<name-of-town>}`

Specify the name of your residence town for the signature field.

To define the path to the logo graphics we require a different workflow: We do not bundle logo graphics with this package due to legal restrictions. They can be downloaded from the University’s website; please note that the website for downloading the logo graphics is only accessible from within the University’s campus network or a VPN connection. To specify the path to the logo graphics, we provide a load-time option to the `se2thesis` class called `logofile` (see Section 3.1).

When printing the thesis in two-side mode—which we recommend—the back of the title page again denotes author and title on the bottom.

`\@lowertitleback` `\@lowertitleback`

Override this internal macro of KOMA-Script to print this information on the back side of the title page.

Additionally, we provide some internal rewritings to standard macros from KOMA-Script that allow to automatically split authors using the `\and` command.

`\author` `\author {<author>}`
`\@author`

We rewrite the definitions of `\author` and `\@author` to do this splitting automatically. Additionally, this also adds a correctly translated version of ‘and’ between the author names if required.

3.3 Type-area settings

The `se2thesis` class manipulates the type area compared to the default settings of the KOMA-Script classes. Our settings are inspired by the `classicthesis` package, which itself is inspired by the style used by famous statistician Edward Tufte. We provide predefined settings for DIN-A4, DIN-A5, and DIN-B5 papers. If you need settings for other paper sizes, please open an issue

on this package's GitHub repository (<https://github.com/se2p/se2thesis>) and we will happily include those settings in a future release of this bundle.

Additionally, we are setting the page footer in a way that it contains the page numbers in the outer margin and the headmarks split from the page numbers by a vertical bar.

3.4 Abstract for the thesis

Each thesis shall come with an abstract that summarises its content. The abstract should be written in the language the thesis is written in. Additionally, there is the requirement to provide a German abstract if the thesis is written in a foreign language.

`\abstract` `\abstract`

We ensure that the `\abstract` command is defined for all document classes.

`abstract (env.)` To typeset an abstract, we provide an environment called `abstract`. The environment takes an optional argument that specifies the language that is used in this abstract. Setting the abstract's language will cause its title to change to the respective language; additionally, hyphenation is also changed for that language.

```
\begin{abstract}[language]
  Your abstract text.
\end{abstract}
```

3.5 Acknowledgements

`acknowledgements (env.)` We provide the `acknowledgements` environment to typeset acknowledgements for your thesis. Using this environment is optional. Usually, bachelor and master thesis do not contain such an acknowledgements section, however, there is no general rule to this.

```
\begin{acknowledgements}[language]
  Your acknowledgements.
\end{acknowledgements}
```

3.6 Document structuring

A larger work, such as a thesis, is usually structured in three large blocks: a frontmatter that provides all the overview, such as abstract, table of contents, etc., a mainmatter that contains all the actual content, and a backmatter for appendices. `se2thesis` ensures that the following macros are defined because they are not provided by all KOMA-Script classes.

`\frontmatter` `\frontmatter`
`\mainmatter` `\mainmatter`
`\backmatter` `\backmatter`

Switches between frontmatter, mainmatter, and backmatter. Most notably, the frontmatter will have roman page numbers, while the other two will have arabic page numbers.

3.7 Authorship declaration

The University of Passau requires its students to provide an authorship declaration as part of their thesis for submission. They provide a template form, which would not fit the style of the `se2thesis` class. Thus, we provide the `\authorshipDeclaration` macro to typeset such a declaration. It uses the original (German) text of the declaration and fills in the values that are specified by the `\author` and `\location` macros.

`\authorshipDeclaration` `\authorshipDeclaration`

Print the authorship declaration text.

Please note: the authorship declaration will always be printed in German, no matter what the language of the thesis is. This happens due to legal requirements. In order to make this work, you have to load the `babel` or `polyglossia` package in a way that it also supports German hyphenation. For example, use

```
\usepackage[ngerman,main=UKenglish]{babel}
```

for a thesis with *traditional English*⁴ as its main language and support for German.

`\signatureBox` `\signatureBox [width] {signature-name}`

A helper macro to print the signature box for the authorship declaration. The optional argument [*width*] allows to specify a custom width for the signature line. The default is 5 cm. The mandatory argument {*signature-name*} specifies the name of the signee, which will be typeset below the signature line.

3.8 Research Questions and findings summaries

Most theses written at our Chair will require the student to provide some empirical evaluation of their work to shed insights whether their proposed ideas are actually useful. For an empirical study, one needs to specify research questions and maybe also hypotheses. The `se2thesis` class supports this by providing environments for this.

- `resq (env.)` The `resq` environment shall be used to specify a research question.
- `hyp (env.)` The `hyp` environment shall be used to specify a hypothesis.
- `summary (env.)` After describing the results, we recommend to give an explicit summary of the findings for a research question or hypothesis. This summary shall be given in one or two sentences. The `summary` environment provides a convenient way for this; it will be typeset in a highlighted box that is easy to spot and also allows readers of the work to quickly grasp the main findings.

```
\begin{summary}{label-reference}  
  The summary text itself.  
\end{summary}
```

The environment expects as a parameter a label, for example, to a research question; however, this can also be arbitrary text.

⁴there is a nice, probably photoshopped, picture of a Steam setup dialogue stating that American English is a 'simplified version' of British English, see <https://jakubmarian.com/is-american-english-simplified-and-british-english-traditional/>.

4 The se2colors package

Several colours are specific to the university and we want to have a comprehensive interface to access them throughout all our packages.

The se2colors package provides this exact features. One can load it using `\usepackage{se2colors}` in the document preamble.





<code>cmode</code>	<code>cmode = <choice></code>
Updated: 2022-11-03	Selects the colour mode that shall be used for creating the results, a choice from the options specified in Table 1. The default setting is 4C.

Table 1: Options provided by se2colors.

























Option	Description
<code>cmode=4C</code>	Define colours in CMYK colour space (<i>default</i>).
<code>cmode=CMYK</code>	Alias for the previous.
<code>CMYK, cmyk</code>	Aliases for the previous.
<code>cmode=RGB</code>	Define colours in RGB colour space.
<code>RGB, rgb</code>	Aliases for the previous.
<code>cmode=BW</code>	Define colours in black-and-white colour space.
<code>cmode=1C</code>	Alias for the previous.
<code>gray</code>	Alias for the previous.





































We define two basic colours that are taken from the University's logo, namely UPSE2-Gray  and UPSE2-Orange .

Additionally, we define four colours for the four faculties of the University:

- the Faculty of Law UPSE2-JUR ,
- the School of Business, Economics and Information Systems UPSE2-WIWI ,
- the Faculty of Arts and Humanities UPSE2-PHIL , and
- the Faculty of Computer Science and Mathematics UPSE2-FIM .

Finally, we define a full set of supplementary colours:

- UPSE2-DarkGray  with its derivatives
UPSE2-DarkGray1 , UPSE2-DarkGray2 , UPSE2-DarkGray3 , UPSE2-DarkGray4 , and
UPSE2-DarkGray5 .
- UPSE2-White  with its derivatives
UPSE2-White1 , UPSE2-White2 , UPSE2-White3 , UPSE2-White4 , and UPSE2-White5 .
- UPSE2-MediumGray  with its derivatives
UPSE2-MediumGray1 , UPSE2-MediumGray2 , UPSE2-MediumGray3 , UPSE2-MediumGray4 , and UPSE2-MediumGray5 .
- UPSE2-LightGray  with its derivatives
UPSE2-LightGray1 , UPSE2-LightGray2 , UPSE2-LightGray3 , UPSE2-LightGray4 ,
and UPSE2-LightGray5 .

- UPSE2-Orange  with its derivatives
UPSE2-Orange1 , UPSE2-Orange2 , UPSE2-Orange3 , UPSE2-Orange4 , and UPSE2-Orange5 .
- UPSE2-LightRed  with its derivatives
UPSE2-LightRed1 , UPSE2-LightRed2 , UPSE2-LightRed3 , UPSE2-LightRed4 , and UPSE2-LightRed5 .
- UPSE2-DarkRed  with its derivatives
UPSE2-DarkRed1 , UPSE2-DarkRed2 , UPSE2-DarkRed3 , UPSE2-DarkRed4 , and UPSE2-DarkRed5 .
- UPSE2-Green  with its derivatives
UPSE2-Green1 , UPSE2-Green2 , UPSE2-Green3 , UPSE2-Green4 , and UPSE2-Green5 .
- UPSE2-Blue  with its derivatives
UPSE2-Blue1 , UPSE2-Blue2 , UPSE2-Blue3 , UPSE2-Blue4 , and UPSE2-Blue5 .
- UPSE2-AccentGray  with its derivatives
UPSE2-AccentGray1 , UPSE2-AccentGray2 , UPSE2-AccentGray3 , UPSE2-AccentGray4 , and UPSE2-AccentGray5 .

5 The se2fonts package

The `se2fonts` package sets the fonts of the document. In the first version of the bundle, we were running to use Hermann Zaph’s *Palatino*, *Helvetica*, and *Neo Euler* fonts. However, we figured out that they are not part of a standard L^AT_EX installation, and thus required manual work by the user to install them. Furthermore, loading the fonts did not always work in a correct way.

Thus, we decided to rethink this decision and—as a consequence—now use different fonts that are part of a recent standard L^AT_EX installation: we use the *Libertinus* fonts⁵ for serif, sans-serif, and math typesetting and the *Inconsolata* font⁶ as a monospaced font.

Please note: this change might affect they way your documents look, and also might affect paragraph and line breaks!

If you are using Lua_T_EX, fonts are expected to be present as open-type fonts; using pdf_L_AT_EX will fallback to Type-1 fonts.

Please note: the package does not support X_YL_AT_EX!

The following options are defined by the `se2fonts` package to influence the selection of the fonts.

The following list provides examples for each of the fonts:

- An example text in Libertinus Serif
- An example text in Libertinus Sans
- An example text in Inconsolata

The package provides additional helper functions that are also available to the user.

```
\pdfteXengine \pdfteXengine
\Xetexengine \Xetexengine
\luatexengine \luatexengine
```

These commands alias the built-in L^AT_EX3 macros `\sys_if_engine_pdfTeX_p:`, `\sys_if_engine_Xetex_p:`, and `\sys_if_engine_luatex_p:`. They can be used to check which engine the user is currently running.

```
\ifengineTF \ifengineTF {<engine>} {<then block>} {<else block>}
\ifengineT \ifengineT {<engine>} {<then block>}
\ifengineF \ifengineF {<engine>} {<then block>}
```

Allows to execute code based on the running engine. The base variant `\ifengineTF` expects the user to specify a condition, which can be built of combinations of the `\pdfteXengine`, `\Xetexengine`, and `\luatexengine` macros, followed by the code that will be executed if the condition holds and the code that will be executed if the condition does not hold.

For convenience, we provide the variants `\ifengineT` and `\ifengineF` that allow to omit an empty then or else branch, respectively.

⁵<https://github.com/alerque/libertinus>

⁶<http://levien.com/type/myfonts/inconsolata.html>

6 The se2packages package

Several packages can be useful for writing a thesis. We provide a simple package for the user that loads these support packages with the recommended options. Please note that you might not need all these packages, however, having a look at them (especially their documentation) might give you an insight whether to use a certain package. Our general recommendation is to use as few packages as you can; some might have conflicts, others basically do the same, or are outdated. Please consider reading the documentation of each package you are using to figure out whether they have any conflicts with other packages (for example, one cannot use the recommended siunitx package together with Slunits) or they might require to be loaded at special places in your preamble (for example, hyperref is usually meant to be loaded as the last package, except you are also using cleveref, which needs to be loaded *after* hyperref).

6.1 The Recommended Packages

We first present the packages we recommend and give a rationale why we believe they should be used. Afterwards, we will discuss how to load the se2packages package to use one or the other of these recommended packages in the next section.

6.1.1 Quoting with csquotes

The csquotes packages allows you for intelligent quoting of text. While verbose quotes are not that common in computer science, the package still provides some useful macros to the user.

6.1.2 Number formatting with siunitx

While siunitx's original purpose was to format physical quantities, it provides a lot of useful features when typesetting theses (and other documents) in computer science. When you skim through its documentation, especiall look at the `\qty` and `\num` macros, as well as the section on typesetting tabular material. We also recommend reading an extensive discussion on number formatting, precision of presented numbers, and more related topics in Beyer et al.'s journal paper on requirements and solutions for reliable benchmarking [1].

6.1.3 Code Listings

We prefer using the minted package for code listings because it provides a lot of options for styling as well as built-in support for a huge number of languages. However, this package requires the installation of Python and the setting of the `-shell-escape` option to your \TeX engine. Please read the package's documentation to set it up; the aforementioned Docker images from the Island of \TeX project provide you everything set up already.

In case you do not want to use the minted package, please consider using listings for typesetting your code listings.

Please be aware to use *either* minted *or* listings!

6.1.4 Designing Tables

A basically mandatory package to all users of tables is the booktabs package. Especially its documentation is a must-read! It provides a large variety of hints for designing tables, most notably that one should never ever use vertical lines; horizontal lines should be used sparsely; booktabs provides three macros for lines that shall be used instead of `\hline` from standard

L^AT_EX: `\toprule` for a rule on the top of a table, above the column heads; `\midrule` to separate column heads and the content, and `\bottomrule` to mark the bottom of a table. We highly recommend that you follow this style when writing your thesis.

Note that captions of tables shall be put *above* the table whereas captions of figures shall go *below* the figure. The rationale is that a figure should be more or less self explaining while a table almost always needs some explanation.

Unfortunately, the distances when using a `\caption` above a table are wrong by default; when creating tables, consider loading the `hvfloats` package and use its `\tabcaption` instead of `\caption` for tables. The `hvfloats` package furthermore provides additional useful macros to typeset all kinds of floats.

6.1.5 Controlling Ligatures, Orphans, and Widows

When using Lua_TE_X (which we recommend anyway), we additionally recommend to use the `selnolig` and `lua-widow-control` packages. The former implements a better control over ligatures, the latter provides better control over orphans and widows.

For some reason we were not yet able to fix properly, `lua-widow-control` works on some machine but fails on others, although they are using the same version of T_EXLive. We therefore deactivate `lua-widow-control` by default.

6.1.6 Use microtype for Microtypographic Optimisation

`microtype` is a game changer when writing documents. While standard L^AT_EX provides reasonably good typography, the `microtype` package brings it to the next level. We refer you to the documentation of the package for details.

Additionally, we prefer to have a thin space around the m-dash. Although we are aware of the discussion whether to have such a space in English, we think it looks more beautiful and thus recommend it.

6.1.7 Use biblatex for Bibliographic References

The standard way of typesetting bibliographic references used to be B_IB_TE_X. The original B_IB_TE_X, however, seems to be very outdated in various ways: it originally only supported 7 bit character sets and creating citation styles requires the usage of a kind of an archaic language. Bib_LA_TE_X resolves many of the drawbacks of B_IB_TE_X; when combined with the `biber` engine, it supports full UTF-8 unicode, therefore correct sorting of the references now works out of the box; also creating citation styles can now be done using simple L^AT_EX commands.

6.1.8 Use cleveref for Internal References

L^AT_EX provides an easy-to-use reference mechanism using the `\label` and `\ref` macros. However, this requires some manual effort and the text needs to specify whether a reference is to a figure, section, or table. We often see in drafts artefacts such as ‘we discuss our findings in 4’; but what is ‘4’ here? Is it a section? A table? A figure?

To avoid such confusion, use the `cleveref` package, which automatically infers the type of the reference (see its documentation on how this works). The `cleveref` package furthermore avoids an additional, common mistake: between the name of the element and its reference one needs to have a non-breaking space that is often forgotten. Instead people are using normal spaces that can break at the end of a line which looks very ugly.

Please note that, in contrast to most other packages, `cleveref` has to be loaded *after* the `hyperref` package!

6.2 Loading se2packages

When you load the `se2packages` package it will automatically load the `csquotes` and `booktabs` packages because we believe that you definitely should use them. Still, it is possible to avoid this by setting the following load-time options to the package.

<code>csquotes</code>	<code>csquotes = $\langle true, false \rangle$</code>
<code>nocsquotes</code>	<code>nocsquotes</code>

The argument to `csquotes` can be one of `true` or `false`. The latter does not load `csquotes`, the former is the default value. By using `nocsquotes` you can also avoid that `csquote` is loaded.

<code>booktabs</code>	<code>booktabs = $\langle true, false \rangle$</code>
<code>nobooktabs</code>	<code>nobooktabs</code>

The argument to `booktabs` can be one of `true` or `false`. The latter does not load `booktabs`, the former is the default value. By using `nobooktabs` you can also avoid that `booktabs` is loaded.

The `siunitx` package is helpful to set quantities and to automatically format numbers consistently. The following load-time option loads it automatically.

<code>siunitx</code>	<code>siunitx = $\langle true, false \rangle$</code>
----------------------	---

Decides whether the package loads `siunitx` and sets the options for `siunitx` to the values we recommend. The default value is `false`, set it to `true` to load `siunitx`.

We provide a load-time option to load `minted` and configure it.

<code>minted</code>	<code>minted = $\langle true, false \rangle$</code>
---------------------	--

Decides whether the package loads `minted` and sets the options for `minted` to the values we recommend. The default value is `false`, set it to `true` to load `minted`. Note that `minted` requires additional installation effort and the use of the `-shell-escape` option, see its documentation.

We also provide a load-time option to load listings and configure it. This option and the `minted` option are mutually exclusive!

<code>listings</code>	<code>listings = $\langle true, false \rangle$</code>
-----------------------	--

Decides whether the package loads `listings` and sets the options for `listings` to the values we recommend. The default value is `false`, set it to `true` to load `listings`.

We provide a load-time option to load `selnolig`.

<code>selnolig</code>	<code>selnolig = $\langle true, false \rangle$</code>
<code>nosealnolig</code>	<code>nosealnolig</code>

The argument to `selnolig` can be one of `true` or `false`. The latter does not load `selnolig`, the former is the default value. By using `nosealnolig` you can also avoid that `selnolig` is loaded.

We provide a load-time option to load `lua-widow-control`.

<code>widowcontrol</code>	<code>widowcontrol = $\langle true, false \rangle$</code>
<code>nowidowcontrol</code>	<code>nowidowcontrol</code>

The argument to `widowcontrol` can be one of `true` or `false`. The former loads `lua-widow-control`, the latter is the default value. By using `nowidowcontrol` you can also avoid that `lua-widow-control` is loaded.

We provide a load-time option to load and configure `microtype`.

`microtype` `microtype = <true,false>`
`nomicrotype` `nomicrotype`

The argument to `microtype` can be one of `true` or `false`. The latter does not load `microtype`, the former is the default value. By using `nomicrotype` you can also avoid that `microtype` is loaded. We provide a load-time option to load and configure `biblatex`.

`biblatex` `biblatex = <true,false,alphabetic,numeric>`

Decides whether the package loads `biblatex` and sets the options for `biblatex` to the values we recommend. The default value is `false`, set it to `true` to load `biblatex`.

By setting the value to `alphabetic`, `se2packages` sets the citation style for `biblatex` to its alphabetic one; selecting `numeric` loads the numeric style as provided by the `acmart` bundle of the ACM. The value `true` also loads the latter style as a default.

Note that for the numeric style, we provide an enhanced `\autocite` command, which does not only print the citation mark in the text but also a short entry listing of the bibliography entry in the margin column of the page. This entry is only printed for the first occurrence of a citation per chapter to not clutter the margin column too much. The other citation commands from `biblatex` work as usual.

Additionally, we provide a load-time option to load `cleveref`. This option makes use of L^AT_EX's hook system to load it as the very last thing in the preamble. You shall not use this option, but load `cleveref` on your own, if your document requires packages that need to be loaded even *after* `cleveref`.

`cleveref` `cleveref = <true,false>`

Decides whether the package load `cleveref`. The default value is `false`, set it to `true` to load `cleveref`.

Lastly, we provide one option to load all recommended packages (with `minted` preferred over `listings`).

`all` `all = <true,false>`

Decides whether the package loads all recommended packages. The default value is `false`, set it to `true` to load them.

6.3 Additional Recommended Packages

The following packages are not part of `se2packages` because they serve a very specific purpose. They might not be needed by many thesis writers, however, we mention them here in order to give you a pointer. We list them in alphabetic order.

- `algorithm2e`: provides tooling for typesetting algorithm diagrams. We recommend loading it with the following options:

```
\usepackage[ruled,noline,noend,linesnumbered]{algorithm2e}
```

- `hvfloating`: a package to control captions, fullpage, and double-page floats. We recommend to load it and use its `\tabcaption` for table captions.
- `lettrine`: allows to start a paragraph with a large initial. This is a beautiful opener for the first paragraph of a thesis' main content.

- `mathtools`: an enhanced version of the famous $\mathcal{A}\mathcal{M}\mathcal{S}$ mathpackage that provides more functionality and fixes some of the known bugs.
- `pdfx`: adds support for PDF/X and PDF/A, which is useful for creating documents that can be archived, for example, by the University’s library.
- `pgfplots`: a library for creating all kinds of plots, based on `pgf`, which is also the basis of the `tikz` package.
- `sidenotesplus`: a package to place all kinds of objects in the margin of a document, from footnotes (then called `sidenotes`) to figures and tables.
- `subcaption`: support for sub-captions and sub-figures.
- `tabularray`: a rewrite of $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ ’s array and tabular abilities in $\text{E}^{\text{T}}\text{E}\text{X}3$. While the package offers a great combination of several other packages’ functionality, it tends to be quite slow for large tables due to the way it is implemented internally.
- `tcolorbox`: allows to typeset coloured boxes, for example, for short summaries on research questions or hypotheses.
- `tikz`: for creating all kinds of figures. Beware: `TikZ` is a really huge package with a lot of functionality and a manual of more than 1300 pages.

References

- [1] Dirk Beyer, Stefan Löwe, and Philipp Wendler: *Reliable benchmarking: requirements and solutions*. STTT 21(1): 1–29 (2019)

Part II

Implementation

The second part of this file provides the implementation of the package for a better understanding of what is happening.

1 Global helpers

These helpers might be useful for many exported packages and classes, thus we keep them on the global level of this implementation.

```
1 <*init>
2   Load only the essential support (expl3) ‘up-front’, and only if required.
3   \ifundefined{ExplLoaderFileDate}
4   { \RequirePackage{expl3} }
5   {}
6   Make sure that the version of l3kernel in use is sufficiently new. We use \ExplFileDate as
7   \ifpackageolder does not work for pre-loaded expl3 in the absence of the package.
8   \ifl@t@r\ExplLoaderFileDate{2020-01-09}
9   {}
10  {%
11  \PackageError{se2colors}{Support package expl3 too old}
12  {%
13  You need to update your installation of the bundles 'l3kernel' and
14  'l3packages'.\MessageBreak
15  Loading~se2colors~will~abort!%
16  }%
17  \endinput
18  }%
```

`\IfFormatAtLeastTF` This macro is not present in older kernels, thus we use the L^AT_EX 2_ε mechanism as this is correct for this case.

```
16 \providecommand \IfFormatAtLeastTF { \ifl@t@r \fmtversion }
17 (End of definition for \IfFormatAtLeastTF. This function is documented on page 2.)
18 </init>
```

2 The se2thesis implementation

Start the DocStrip guards.

```
18 <*class>
19   Identify the internal prefix (LATEX3 DocStrip convention): only internal material in this
20   submodule should be used directly.
21   <@=slcd>
22   Identify the class and give the overall version number.
23   \ProvidesExplClass {se2thesis} {2024-02-22} {3.3.0}
24   {A thesis class for the Chair of Software Engineering II}
```

`\slcd_package_if_loaded:nTF` Defines various L^AT_EX3 variants for the internal `\ifpackageloaded` macro to check whether a package has been loaded.

```
\slcd_package_if_loaded:nTF
\slcd_package_if_loaded:nT
\slcd_package_if_loaded:nF
\slcd_package_if_loaded:p:n
22 \prg_new_conditional:Nnn \slcd_package_if_loaded:n { p, T, F, TF }
23 {
24   \use:c { @ifpackageloaded }
25   { #1 }
26   { \prg_return_true: }
27   { \prg_return_false: }
28 }
```

(End of definition for `\slcd_package_if_loaded:nTF` and others. These functions are documented on page 2.)

Load required packages early.

```
29 \RequirePackage{graphicx}
30 \RequirePackage{translations}
31 \LoadDictionary{se2translations}
32 \DeclareTranslationFallback{version-of-date}{%
33   Version~\l__slcd_version_tl\ of~\@date
34 }
35 \DeclareTranslation{German}{version-of-date}{%
36   Version~\l__slcd_version_tl\ vom~\@date
37 }
38 \DeclareTranslation{English}{version-of-date}{%
39   Version~\l__slcd_version_tl\ of~\@date
40 }
```

2.1 Define Variables

The following variables are necessary for the argument handling.

`\l__slcd_paper_int` A variable to store the key of the page size selected by the user.

```
41 \int_new:N \l__slcd_paper_int
```

(End of definition for `\l__slcd_paper_int`.)

We also need properties to store class options that are not for us, thus shall be handled by the underlying base class.

`\l__slcd_base_class_tl` Store the known and the unknown class options. The latter will be forwarded to the base class later.

```
\l__slcd_clsopts_prop
\l__slcd_unknown_clsopts_prop
42 \tl_new:N \l__slcd_base_class_tl
43 \prop_new:N \l__slcd_clsopts_prop
44 \prop_new:N \l__slcd_unknown_clsopts_prop
```

(End of definition for `\l__slcd_base_class_tl`, `\l__slcd_clsopts_prop`, and `\l__slcd_unknown_clsopts_prop`.)

Define internal variables to hold the values of the fields of the title page.

```
\l__slcd_version_tl
\l__slcd_degreeprogramme_tl
\l__slcd_matrnumber_tl
\l__slcd_supervisor_tl
\l__slcd_cosupervisor_tl
\l__slcd_advisor_tl
\l__slcd_coadvisor_tl
\l__slcd_department_tl
\l__slcd_institute_tl
\l__slcd_external_tl
\l__slcd_logofile_tl
\l__slcd_signature_tl
\l__slcd_location_tl
45 \tl_new:N \l__slcd_version_tl
46 \tl_new:N \l__slcd_degreeprogramme_tl
47 \tl_new:N \l__slcd_matrnumber_tl
48 \tl_new:N \l__slcd_supervisor_tl
49 \tl_new:N \l__slcd_cosupervisor_tl
50 \tl_new:N \l__slcd_advisor_tl
51 \tl_new:N \l__slcd_coadvisor_tl
52 \tl_new:N \l__slcd_department_tl
53 \tl_new:N \l__slcd_institute_tl
54 \tl_new:N \l__slcd_external_tl
55 \tl_new:N \l__slcd_logofile_tl
56 \tl_new:N \l__slcd_signature_tl
57 \tl_new:N \l__slcd_location_tl
```

(End of definition for `\l__slcd_version_tl` and others.)

Define several dimensions for the typearea package to define the package style.

```

\l__slcd_marginspace_dim
\l__slcd_headmarkspace_dim 58 \dim_new:N \l__slcd_marginspace_dim
\l__slcd_rulespace_dim      59 \dim_new:N \l__slcd_headmarkspace_dim
\l__slcd_pagemark_minipage_dim 60 \dim_new:N \l__slcd_rulespace_dim
\l__slcd_rulerraise_dim     61 \dim_new:N \l__slcd_pagemark_minipage_dim
\l__slcd_rulewidth_dim      62 \dim_new:N \l__slcd_rulerraise_dim
\l__slcd_rulethickness_dim  63 \dim_new:N \l__slcd_rulewidth_dim
64 \dim_new:N \l__slcd_rulethickness_dim
65 \dim_gset:Nn \l__slcd_marginspace_dim { -1.85cm }
66 \dim_gset:Nn \l__slcd_headmarkspace_dim { 0.75cm }
67 \dim_gset:Nn \l__slcd_rulespace_dim { 10pt }
68 \dim_gset:Nn \l__slcd_pagemark_minipage_dim { 1.5cm }
69 \dim_gset:Nn \l__slcd_rulerraise_dim { -5pt }
70 \dim_gset:Nn \l__slcd_rulewidth_dim { 1.25pt }
71 \dim_gset:Nn \l__slcd_rulethickness_dim { 15pt }

```

(End of definition for \l__slcd_marginspace_dim and others.)

2.2 Load-time options

We define the key-value interface for the class.

```

\l__slcd_base_class_tl
\l_slcd_unknown_clsopts_prop 72 \keys_define:nn { seiithesis }
\l__slcd_paper_int           73 {
\l__slcd_thesis_type_tl     74   class .choice:,
\l__slcd_license_type_tl    75   class / report .meta:n = {class=scrreprt},
\l_slcd_licensemodifier_tl  76   class / scrreprt .code:n = \tl_gset:Nn \l__slcd_base_class_tl {scrreprt},
\l__slcd_licenseversion_tl  77   class / book .meta:n = {class=scrbook},
\l__slcd_colormode_tl       78   class / scrbook .code:n = \tl_gset:Nn \l__slcd_base_class_tl {scrbook},
79   class .initial:n = scrbook,
80
81   paper .choices:nn = {a4,b5}{
82     \int_gset_eq:NN \l__slcd_paper_int \l_keys_choice_int
83   },
84   paper .initial:n = a4,
85
86   logfile .tl_gset:N = \l__slcd_logofile_tl,
87   logfile .initial:n = ,
88
89   thesistype .choice:,
90   thesistype / bachelor .code:n = \tl_gset:Nn \l__slcd_thesis_type_tl {bachelor},
91   thesistype / bachelorproposal .code:n = {
92     \tl_gset:Nn \l__slcd_thesis_type_tl {bachelorproposal}
93   },
94   thesistype / master .code:n = \tl_gset:Nn \l__slcd_thesis_type_tl {master},
95   thesistype / masterproposal .code:n = {
96     \tl_gset:Nn \l__slcd_thesis_type_tl {masterproposal}
97   },
98   thesistype / phd .code:n = \tl_gset:Nn \l__slcd_thesis_type_tl {phd},
99   thesistype / phdeng .code:n = \tl_gset:Nn \l__slcd_thesis_type_tl {phdeng},
100  thesistype / phdproposal .code:n = {
101    \tl_gset:Nn \l__slcd_thesis_type_tl {phdproposal}
102  },

```

```

103 thesistype .initial:n = master,
104
105 colormode .choices:nn = {cmyk,rgb,bw}{
106   \tl_gset_eq:NN \l__slcd_colormode_tl \l_keys_choice_tl
107 },
108 colormode .initial:n = cmyk,
109
110 unknown .code:n = {
111   \prop_gput:NvN \l__slcd_unknown_clsopts_prop \l_keys_key_tl {#1}
112 },
113 }

```

(End of definition for \l__slcd_base_class_tl and others.)

Handle the options

```

114 \IfFormatAtLeastTF { 2022-06-01 }
115 { \ProcessKeyOptions [ seiithesis ] }
116 {
117   \RequirePackage{ l3keys2e }
118   \ProcessKeysOptions { seiithesis }
119 }

```

Handle the known options for base class

```

120 \prop_map_inline:Nn \l__slcd_clsopts_prop
121 {
122   \tl_if_empty:nTF {#2}
123   { \PassOptionsToClass {#1} {\l__slcd_base_class_tl} }
124   {
125     \clist_map_inline:nn {#2}
126     { \PassOptionsToClass {#1=#1} {\l__slcd_base_class_tl} }
127   }
128 }

```

Load the base class

```

129 \LoadClass{\l__slcd_base_class_tl}

```

Attempt to handle the unknown options

```

130 \prop_map_inline:Nn \l__slcd_unknown_clsopts_prop
131 {
132   \cs_if_exist:cT {KV@KOM.A.\l__slcd_base_class_tl.cls@#1}
133   {
134     \tl_if_empty:nTF {#2}
135     { \KOMAOptions{#1} }
136     { \KOMAOption{#1}{#2}}
137   }
138 }

```

2.3 Package loading

We load some packages with options that depend on options to the se2thesis class. Thus, we load them here to be able to hand them over the respective values.

We start with the se2colors and se2fonts packages.

```

139 \PassOptionsToPackage{\l__slcd_colormode_tl}{se2colors}
140 \RequirePackage{se2colors}
141
142 \RequirePackage{se2fonts}

```

2.4 User macros for the title page

In addition to the macros provided by the KOMA-Script classes for the title-page values (e.g. `\author`, `\title`), provide these additional macros to the user.

`\version` Specify the version of the document, e.g., a git hash.

```
143 \ProvideDocumentCommand \version { m }
144 {
145   \tl_set:Nn \l__slcd_version_tl {#1}
146 }
```

(End of definition for `\version`. This function is documented on page 3.)

`\degreeprogramme` Specify the degree programme the thesis is meant to be accepted in.

```
147 \ProvideDocumentCommand \degreeprogramme { m }
148 {
149   \tl_set:Nn \l__slcd_degreeprogramme_tl {#1}
150 }
```

(End of definition for `\degreeprogramme`. This function is documented on page 3.)

`\matrnumber` Specify the matriculation number of the student.

```
151 \ProvideDocumentCommand \matrnumber { m }
152 {
153   \tl_set:Nn \l__slcd_matrnumber_tl {#1}
154 }
```

(End of definition for `\matrnumber`. This function is documented on page 3.)

`\supervisor` Specify the supervisor and co-supervisor of the thesis, usually a professor.
`\cosupervisor`

```
155 \ProvideDocumentCommand \supervisor { m }
156 {
157   \tl_set:Nn \l__slcd_supervisor_tl {#1}
158 }
159 \ProvideDocumentCommand \cosupervisor { m }
160 {
161   \tl_set:Nn \l__slcd_cosupervisor_tl {#1}
162 }
```

(End of definition for `\supervisor` and `\cosupervisor`. These functions are documented on page 4.)

`\advisor` Specify the advisor and co-advisor of the thesis, usually a PhD student or postdoc.
`\coadvisor`

```
163 \ProvideDocumentCommand \advisor { m }
164 {
165   \tl_set:Nn \l__slcd_advisor_tl {#1}
166 }
167 \ProvideDocumentCommand \coadvisor { m }
168 {
169   \tl_set:Nn \l__slcd_coadvisor_tl {#1}
170 }
```

(End of definition for `\advisor` and `\coadvisor`. These functions are documented on page 4.)

`\department` Specify the university's department and institute you are writing the thesis for.

```
\institute
171 \ProvideDocumentCommand \department { m }
172 {
173   \tl_set:Nn \l__slcd_department_tl {#1}
174 }
175 \ProvideDocumentCommand \institute { o m }
176 {
177   \tl_set:Nn \l__slcd_institute_tl {#2}
178 }
```

(End of definition for `\department` and `\institute`. These functions are documented on page 4.)

`\external` Specify an external referee.

```
179 \ProvideDocumentCommand \external { m }
180 {
181   \tl_set:Nn \l__slcd_external_tl {#1}
182 }
```

(End of definition for `\external`. This function is documented on page 4.)

`\location` Specify the location for the signature field.

```
183 \ProvideDocumentCommand \location { m }
184 {
185   \tl_set:Nn \l__slcd_location_tl {#1}
186 }
```

(End of definition for `\location`. This function is documented on page 4.)

2.5 Define logo, paper size, and paper style

For the logo on the titlepage, we define further variables to store its height and a box to store the logo itself.

```
\l__slcd_logo_height_dim
\l__slcd_logo_box
187 \dim_if_exist:NF \l__slcd_logo_height_dim
188 {
189   \dim_new:N \l__slcd_logo_height_dim
190   \int_compare:nTF { \l__slcd_paper_int=1 }
191     {
192       \dim_gset:Nn \l__slcd_logo_height_dim { 67.5pt }
193     } {
194       \dim_gset:Nn \l__slcd_logo_height_dim { 56.8pt }
195     }
196 }
197 \box_if_exist:NF \l__slcd_logo_box
198 {
199   \box_new:N \l__slcd_logo_box
200 }
201 \tl_if_empty:NF \l__slcd_logofile_tl
202 {
203   \hbox_gset:Nn \l__slcd_logo_box
204     {
205       \includegraphics[%
206         height=\l__slcd_logo_height_dim%
```



```

207     ]{\l__slcd_logofile_tl}
208   }
209 }

```

(End of definition for \l__slcd_logo_height_dim and \l__slcd_logo_box.)

Set the paper size depending on the selected paper option.

```

210 \int_compare:nTF { \l__slcd_paper_int=1 }
211 {
212   \areaset[current]{350pt}{567pt}
213   \setlength{\marginparsep}{8.5cm}
214   \setlength{\marginparsep}{1em}
215 }{
216   \areaset[current]{350pt}{567pt}
217   \setlength{\marginparsep}{7.4cm}
218   \setlength{\marginparsep}{0.87em}
219 }

```

Provide the package style. We start by loading the `scrlayer-scrpage` package with the appropriate options and set some basic properties.

```

220 \PassOptionsToPackage{automark}{scrlayer-scrpage}
221 \RequirePackage{scrlayer-scrpage}
222 \clearpaairofpagestyles
223 \setkomafont{pagefoot}{\normalfont\sffamily}

```

We can then define the footer for odd pages, which will appear on the right side of the page's footer. This definition contains first, as an optional argument, the style of a page with `pagestyle` set to empty, i.e., a page where a new chapter starts, and afterwards the style of a regular right-hand side page.

```

224 \rofoot[{%
225   \group_begin: \ \group_end:
226   \footnotesize%
227   \hspace*{\l__slcd_headmarkspace_dim}%
228   \group_begin:
229     \color{UPSE2-Blue}%
230     \rule[\l__slcd_ruleraise_dim]{\l__slcd_rulewidth_dim}{\l__slcd_rulethickness_dim}%
231   \group_end:
232   \hspace*{\l__slcd_rulespace_dim}%
233   \begin{minipage}[b]{\l__slcd_pagemark_minipage_dim}%
234     \normalsize\textbf{\pagemark}%
235   \end{minipage}%
236   \hspace{\l__slcd_marginspace_dim}%
237 ]]{%
238   \group_begin: \ \group_end:
239   \footnotesize%
240   \group_begin:
241     \color{UPSE2-Blue}\headmark
242   \group_end:
243   \hspace*{\l__slcd_rulespace_dim}%
244   \group_begin:
245     \color{UPSE2-Blue}%
246     \rule[\l__slcd_ruleraise_dim]{\l__slcd_rulewidth_dim}{\l__slcd_rulethickness_dim}%
247   \group_end:
248   \hspace*{\l__slcd_rulespace_dim}%
249   \begin{minipage}[b]{\l__slcd_pagemark_minipage_dim}%
250     \normalsize\textbf{\pagemark}%

```

```

251 \end{minipage}%
252 \hspace{\l__slcd_marginspace_dim}%
253 }

```

Similarly, we define the footer for even pages, which will appear on the left side of the page's footer.

```

254 \leftfoot[{\%
255 \null\hspace{\l__slcd_marginspace_dim}%
256 \footnotesize%
257 \begin{minipage}[b]{\l__slcd_pagemark_minipage_dim}%
258 \raggedleft\normalsize\textbf{\pagemark}%
259 \end{minipage}%
260 \footnotesize%
261 \hspace*{\l__slcd_rulespace_dim}%
262 \group_begin:
263 \color{UPSE2-Blue}%
264 \rule[\l__slcd_ruleraise_dim]{\l__slcd_rulewidth_dim}{\l__slcd_rulethickness_dim}%
265 \group_end:
266 ]]{\%
267 \null\hspace{\l__slcd_marginspace_dim}%
268 \footnotesize%
269 \begin{minipage}[b]{\l__slcd_pagemark_minipage_dim}%
270 \raggedleft\normalsize\textbf{\pagemark}%
271 \end{minipage}%
272 \footnotesize%
273 \hspace*{\l__slcd_rulespace_dim}%
274 \group_begin:
275 \color{UPSE2-Blue}%
276 \rule[\l__slcd_ruleraise_dim]{\l__slcd_rulewidth_dim}{\l__slcd_rulethickness_dim}%
277 \group_end:
278 \hspace*{\l__slcd_headmarkspace_dim}%
279 \group_begin:
280 \color{UPSE2-Blue}\headmark
281 \group_end:
282 }

```

Finally, set the page style.

```

283 \pagestyle{scrheadings}

```

2.6 The title page

We start out by adjusting some KOMA-Script fonts.

```

284 \setkomafont{title}{\Huge}
285 \setkomafont{subtitle}{\Large}
286 \setkomafont{subject}{\normalsize}
287 \setkomafont{author}{\large}
288 \setkomafont{date}{\normalsize}
289 \setkomafont{publishers}{\normalsize}

```

`\author` Allow for automated splitting of author's names.

```

\@author
290 \seq_new:N \l__slcd_author_seq
291 \renewcommand*\author[2][{}{
292 \seq_gset_split:Nnn \l__slcd_author_seq {\and} {#2}
293 \tl_if_empty:nTF {#1}

```

```

294 { \tl_set:Nn \l__slcd_signature_tl {#2} }
295 { \tl_set:Nn \l__slcd_signature_tl {#1} }
296 }
297 \renewcommand*{\@author}{
298   \group_begin:
299   \hyphenpenalty=100000
300   \seq_use:Nnnn \l__slcd_author_seq {\~\GetTranslation{and}~} {,~} {\~\&~}
301   \group_end:
302 }

```

(End of definition for \@author and \@author. These functions are documented on page 4.)

Define a new layer using the functionality from sclayer-scrpage for the logo image.

```

303 \DeclareNewLayer[
304   mode=picture,
305   foreground,
306   align=tr,
307   hoffset=\oddsidemargin+1.5in+\textwidth,
308   voffset=\coverpagetopmargin+1.5in+\ht\strutbox,
309   width=\textwidth - \box_wd:N \l__slcd_logo_box,
310   height=\box_ht:N \l__slcd_logo_box,
311   contents={\putUL{\box_use:N \l__slcd_logo_box}},
312 ]{title.seii.logo}
313 \DeclareNewPageStyleByLayers{title.seii}{title.seii.logo}
314 \renewcommand*{\titlepagestyle}{title.seii}

```

Redefine the \maketitle command. The following code is an adapted version of the corresponding KOMA-Script macro by Markus Kohm.

```

315 \renewcommand*{\maketitle}[1][1]{
316   \begin{titlepage}
317     \setcounter{page}{#1}
318     \def\thefootnote{\fnsymbol{footnote}}
319     \edef\titlepage@restore{%
320       \noexpand\endgroup
321       \noexpand\global\noexpand\colht\the\colht
322       \noexpand\global\noexpand\colroom\the\colroom
323       \noexpand\global\vsizethe\vsizethe
324       \noexpand\global\noexpand\@titlepageiscoverpagefalse
325       \noexpand\let\noexpand\titlepage@restore\noexpand\relax
326     }%
327     \begingroup
328     \topmargin=\dimexpr \coverpagetopmargin-1in\relax
329     \oddsidemargin=\dimexpr 0in\relax
330     \evensidemargin=\dimexpr 0in\relax
331     \textwidth=\dimexpr \paperwidth-2in\relax
332     \textheight=\dimexpr
333     \paperheight-\coverpagetopmargin-\coverpagebottommargin\relax
334     \headheight=0pt
335     \headsep=0pt
336     \footskip=\baselineskip
337     \@colht=\textheight
338     \@colroom=\textheight
339     \vsizethe=\textheight
340     \columnwidth=\textwidth
341     \hsizethe=\textwidth

```

```

342 \linewidth=\hsize
343 \setparsizes{\z@}{\z@}{\z@\@plus 1fil}\par@updaterelative
344 \thispagestyle{title.seii}
345 %
346 \@maketitle
347 %
348 \if@twoside
349 \@tempwatrue
350 \if@tempswa
351 \next@tpage
352 \begin{minipage}[t]{\textwidth}
353 \@uppertitleback
354 \end{minipage}
355 \vfill
356 \begin{minipage}[b]{\textwidth}
357 \@lowertitleback
358 \end{minipage}\par
359 \@thanks\let\@thanks\@empty
360 \fi
361 \fi
362 \ifx\titlepage@restore\relax\else\clearpage\titlepage@restore\fi
363 \end{titlepage}
364 }

```

`\l__slcd_title_box` Define a box for the title if it does not yet exist.

```

365 \box_if_exist:NF \l__slcd_title_box
366 {
367 \box_new:N \l__slcd_title_box
368 }

```

(End of definition for \l__slcd_title_box.)

`\@maketitle` Redeclare the `\@maketitle` macro.

```

369 \renewcommand*{\@maketitle}{%
370 \group_begin:
371 \setparsizes{\z@}{\z@}{\z@\@plus 1fil}\par@updaterelative
372 \thispagestyle{title.seii}
373 \hbox_gset:Nn \l__slcd_title_box
374 {
375 \parbox{\textwidth}{\l__slcd_print_title:}
376 }
377 \null
378 \skip_vertical:n { 2.5 \box_ht:N \l__slcd_logo_box }
379 \box_use:N \l__slcd_title_box
380 \skip_vertical:n { .5 \box_ht:N \l__slcd_logo_box }
381 \group_end:
382 \@thanks\let\@thanks\@empty
383 }

```

(End of definition for \@maketitle. This function is documented on page 3.)

Load the `ifthen` package.

```

384 \RequirePackage{ifthen}

```

Prints the title formatted appropriately. We start with printing the title, optional subtitle, and the author names.

```

385 \cs_new:Nn \__slcd_print_title:
386 {
387   \group_begin:
388     \usekomafont{title}\centering\@title\par
389   \group_end:
390   \ifx\@subtitle\empty\else%
391     \medskip\usekomafont{subtitle}\centering\@subtitle\par%
392   }\fi
393   \bigskip
394   \group_begin:
395     \usekomafont{author}\centering\@author\par
396   \group_end:
397   \bigskip

```

The next block generates the text that describes the thesis. In case of a PhD thesis, this text is predefined to match the requirements. In case of a bachelor or master thesis, or a proposal thereof, we generate a text based on the values of the `thesistype` load-time option and the values of the `\degreeprogramme`, `\department`, and `\institute` variables.

```

398   \exp_args:NV
399   {
400     \begin{center}
401       \tl_if_eq:NnTF \l__slcd_thesis_type_tl { phd }
402       {
403         Dissertation zur Erlangung des Doktorgrades\\
404         der Naturwissenschaften (Dr.\,rer.\,nat.)\\
405         eingereicht an der Fakultät für Informatik und Mathematik\\
406         der Universität Passau\\
407         \rule{\textwidth}{.1pt}\\
408         Dissertation submitted to\\
409         the Faculty of Computer Science and Mathematics\\
410         of the University of Passau\\
411         in partial fulfillment of obtaining\\
412         the degree of a Doctor of Natural Sciences
413       } {
414         \tl_if_eq:NnTF \l__slcd_thesis_type_tl { phdeng }
415         {
416           Dissertation zur Erlangung des Doktorgrades\\
417           der Ingenieurwissenschaften (Dr.-Ing.)\\
418           eingereicht an der Fakultät für Informatik und Mathematik\\
419           der Universität Passau\\
420           \rule{\textwidth}{.1pt}\\
421           Dissertation submitted to\\
422           the Faculty of Computer Science and Mathematics\\
423           of the University of Passau\\
424           in partial fulfillment of obtaining\\
425           the degree of a Doctor of Engineering
426         } {
427           \tl_if_eq:NnT \l__slcd_thesis_type_tl { bachelor }
428           { \GetTranslation{Bachelor-thesis} }
429           \tl_if_eq:NnT \l__slcd_thesis_type_tl { bachelorproposal }
430           { \GetTranslation{Bachelor-thesis-proposal} }
431           \tl_if_eq:NnT \l__slcd_thesis_type_tl { master }

```

```

432         { \GetTranslation{Master-thesis} }
433     \tl_if_eq:NnT \l__slcd_thesis_type_tl { masterproposal }
434         { \GetTranslation{Master-thesis-proposal} }
435     \tl_if_eq:NnT \l__slcd_thesis_type_tl { phdproposal }
436         { \GetTranslation{PhD-thesis-proposal} }
437     \tl_if_empty:NF \l__slcd_degreeprogramme_tl
438         {
439         \ in~\l__slcd_degreeprogramme_tl
440         }
441     \par
442     \tl_if_empty:NF \l__slcd_department_tl { \l__slcd_department_tl \par }
443     \tl_if_empty:NF \l__slcd_institute_tl { \l__slcd_institute_tl \par }
444 }
445 }
446 \end{center}\par\bigskip

```

Finally, generate a table with information about supervisors, advisors, etc.

```

447 \begin{center}
448 \begin{tabular}{@{} l @{\quad} l}
449     \tl_if_empty:NF \l__slcd_matrnumber_tl
450     {
451         \GetTranslation{Matrnumber} & \l__slcd_matrnumber_tl \\
452     }
453     \tl_if_empty:NF \l__slcd_supervisor_tl
454     {
455         \GetTranslation{Supervisor} & \l__slcd_supervisor_tl \\
456     }
457     \tl_if_empty:NF \l__slcd_cosupervisor_tl
458     {
459         \GetTranslation{Co-supervisor} & \l__slcd_cosupervisor_tl \\
460     }
461     \tl_if_empty:NF \l__slcd_advisor_tl
462     {
463         \GetTranslation{Advisor} & \l__slcd_advisor_tl \\
464     }
465     \tl_if_empty:NF \l__slcd_coadvisor_tl
466     {
467         \GetTranslation{Co-advisor} & \l__slcd_coadvisor_tl \\
468     }
469     \tl_if_empty:NF \l__slcd_external_tl
470     {
471         \GetTranslation{External} & \l__slcd_external_tl \\
472     }
473 \end{tabular}
474 \end{center}
475 \par\medskip

```

Last, print the date or the version.

```

476 \group_begin:
477     \usekomafont{date}
478     \centering
479     \tl_if_empty:NTF \l__slcd_version_tl
480     { \@date }
481     { \GetTranslation{version-of-date} }
482 \par\smallskip

```

```

483     \group_end:
484     }
485 }

```

`\@lowertitleback` Afterwards, override the definition of `\@lowertitleback`.

```

486 \renewcommand*{\@lowertitleback}{%
487   \group_begin:
488     \noindent\textbf{\@author}:\!
489     \emph{\@title}\!
490     \tl_if_eq:NnT \l__slcd_thesis_type_tl { bachelor }
491     { \GetTranslation{Bachelor-thesis},~ }
492     \tl_if_eq:NnT \l__slcd_thesis_type_tl { master }
493     { \GetTranslation{Master-thesis},~ }
494     \tl_if_eq:NnT \l__slcd_thesis_type_tl { phd }
495     { \GetTranslation{PhD-thesis},~ }
496     \Translation{up},~\the\year.
497   \group_end:
498 }

```

(End of definition for \@lowertitleback. This function is documented on page 4.)

2.7 Styling of the sectioning commands

We change the formatting of the chapter, section, and sub-section headings.

```

499 \addtokomafont{chapterprefix}{\raggedleft\bfseries}
500 \addtokomafont{chapter}{\mdseries}
501 \addtokomafont{section}{\large\mdseries}
502 \addtokomafont{subsection}{\normalsize\mdseries}
503 \renewcommand*{\chapterformat}{%
504   \enskip\mbox{%
505     \scalebox{3}{\color{UPSE2-DarkGray}\thechapter\autodot}%
506   }%
507 }
508 \renewcommand{\chapterlinesformat}[3]{%
509   \parbox[b]{\textwidth}{\hrulefill#2}\par%
510   #3\par\bigskip%
511   \hrule%
512 }
513 \RedeclareSectionCommand[afterskip=1.5\baselineskip]{chapter}
514 \renewcommand*{\chapterlineswithprefixformat}[3]{%
515   \Ifstr{#1}{chapter}
516     {#2\textls*[75]{\MakeUppercase{#3}}}% change definition for chapter
517     {#2#3}% original definition
518 }%
519 \renewcommand*{\sectionlinesformat}[4]{%
520   #3\textls*[75]{\MakeUppercase{#4}}%
521 }

```

Change the loop of a `\paragraph` to be italic and end with a full stop.

```

522 \setkomafont{paragraph}{\normalsize\normalfont\itshape}
523 \AddtoDoHook{heading/endgroup/paragraph}{\headingdot}
524 \newcommand*{\headingdot}[1]{.}

```

Change the width of a dictum

```

525 \renewcommand*{\dictumwidth}{0.42\linewidth}

```

2.8 Provide an environment for abstracts

We want to allow abstracts in German and English, which is also a requirement when writing a thesis in English. First, ensure that the `\abstract` macro is available for all classes.

`\abstract`

```
526 \providecommand{\abstract}{}
```

(End of definition for `\abstract`. This function is documented on page 5.)

Then redefine the `abstract` environment such that it provides an optional argument for language selection.

`abstract (env.)` Used to typeset an abstract for the thesis. The optional argument allows to specify a language. As a default the current document language will be used.

```
527 \RenewDocumentEnvironment { abstract } { o }
528 {
529   \group_begin:
530   \IfNoValueF {#1} { \selectlanguage{#1} }
531   \scr@ifundefinedorrelax{chapter}{
532     \Iftocfeature{toc}{leveledown}
533     {\subsection*}
534     {\section*}
535   }{
536     \let\clearpage\relax
537     \Iftocfeature{toc}{leveledown}
538     {\section*}
539     {\chapter*}
540   } { \GetTranslation{Abstract} }
541 } {
542   \group_end:
543 }
```

2.9 Provide an environment for acknowledgements

Often, especially in a PhD thesis, one wants to acknowledge the help of certain people, for example, supervisors, family, and friends.

`acknowledgements (env.)` Use to typeset the acknowledgements for the thesis.

```
544 \NewDocumentEnvironment { acknowledgements } { o }
545 {
546   \group_begin:
547   \IfNoValueF {#1} { \selectlanguage{#1} }
548   \scr@ifundefinedorrelax{chapter}{
549     \Iftocfeature{toc}{leveledown}
550     {\subsection*}
551     {\section*}
552   }{
553     \Iftocfeature{toc}{leveledown}
554     {\section*}
555     {\chapter*}
556   } { \GetTranslation{Acknowledgements} }
557 } {
558   \group_end:
559 }
```


2.10 Document structuring macros

Ensure that these macros are defined. These are the exact definitions from KOMA-Script.

```
560 \newif\if@mainmatter\@mainmattertrue
```

`\frontmatter` Starts the frontmatter. Most notably, set the page numbers to roman.

```
561 \providecommand*\frontmatter{
562   {
563     \if@twoside\cleardoubleoddpages\else\clearpage\fi
564     \@mainmatterfalse
565     \pagenumbering { roman }
566   }
```

(End of definition for \frontmatter. This function is documented on page 5.)

`\mainmatter` Starts the mainmatter or the backmatter. Most notably, set the page numbers to arabic.

`\backmatter`

```
567 \providecommand*\mainmatter{
568   {
569     \if@twoside\cleardoubleoddpages\else\clearpage\fi
570     \@mainmattertrue
571     \pagenumbering { arabic }
572   }
573 \providecommand*\backmatter{
574   {
575     \if@twoside\cleardoubleoddpages\else\clearpage\fi
576     \@mainmatterfalse
577   }
```

(End of definition for \mainmatter and \backmatter. These functions are documented on page 5.)

2.11 Declaration of authorship

`\authorshipDeclaration` Provide a command to typeset the authorship declaration.

```
578 \NewDocumentCommand \authorshipDeclaration { o }
579 {
580   \par
581   \group_begin:
582     \selectlanguage{ngerman}
583     \IfNoValueF {#1}
584       { \tl_gset:Nn \l__slcd_location_tl {#1} }
585
586   \tl_if_empty:NT \l__slcd_location_tl
587     {
588       \msg_new:nnn { seiithesis }
589         { no-location-specified }
590       {
591         You~ need~ to~ specify~ a~ location~ for~ the~ authorship~
592         declaration.~ Either~ via~ the~ location~ macro~ or~ via~ the~
593         optional~ argument~ of~ the~ authorshipDeclaration~ macro.
594       }
595       \msg_warning:nn { seiithesis } { no-location-specified }
596     }
597
598   \scr@ifundefinedorrelax{chapter}{
```

```

599     \Iftocfeature{toc}{leveldown}
600     {\subsection*}
601     {\section*}
602   }{
603     \Iftocfeature{toc}{leveldown}
604     {\section*}
605     {\chapter*}
606   } { Eigenständigkeitserklärung }
607
608   Hiermit~ versichere~ ich,~ \l__slcd_signature_tl,
609   \begin{enumerate}
610     \item dass~ ich~ die~ vorliegende~ Arbeit~ selbstständig~ und~ ohne~
611     unzulässige~ Hilfe~ verfasst~ und~ keine~ anderen~ als~ die~
612     angegebenen~ Quellen~ und~ Hilfsmittel~ benutzt,~ sowie~ die~
613     wörtlich~ und~ sinngemäß~ übernommenen~ Passagen~ aus~ anderen~
614     Werken~ kenntlich~ gemacht~ habe.
615     \item Außerdem~ erkläre~ ich,~ dass~ ich~ der~ Universität~ ein~
616     einfaches~ Nutzungsrecht~ zum~ Zwecke~ der~ Überprüfung~ mittels~
617     einer~ Plagiatssoftware~ in~ anonymisierter~ Form~ einräume.
618   \end{enumerate}\par
619   \bigskip
620   \noindent \l__slcd_location_tl,~ \@date\hfill
621   \signatureBox{\l__slcd_signature_tl}
622   \group_end:
623   \\strut\cleardoublepage
624   }

```

(End of definition for \authorshipDeclaration. This function is documented on page 6.)

`\signatureBox` Provide a box for the signature.

```

625 \newcommand*{\signatureBox}[2][5cm]{
626   \parbox[t]{#1}{
627     \centering
628     \rule{\linewidth}{.3pt}\makebox[0pt][c]{#2}
629   }
630 }

```

(End of definition for \signatureBox. This function is documented on page 6.)

2.12 Research questions and summary boxes

We utilise the `ntheorem` package for defining new theorem environments that are used for defining research questions and hypotheses. Therefore, start with loading this package. `ntheorem`.

```

631 \slcd_package_if_loaded:nT { amsmath }
632 {
633   \PassOptionsToPackage{amsmath}{ntheorem}
634 }
635 \RequirePackage{ntheorem}
636 \theoremseparator{:}

```

`resq (env)` We can then define the `resq` and `hyp` environments using the `\newtheorem` macro from `ntheorem`.

```

637 \hyp (env) \newtheorem{resq}{Research~ Question}
638 \newtheorem{hyp}{Hypothesis}

```

For the summary boxes, we utilise the tcolorbox package. We start with loading this package.

```
639 \RequirePackage{tcolorbox}
```

summary (*env.*) The summary environment expects a label and has the summary text in its content.

```
640 \NewDocumentEnvironment { summary } { m }
641 { \begin{tcolorbox}[title={Summary~ (#1)}] }
642 { \end{tcolorbox} }

643 \endclass
```

3 Translations for se2thesis

```
644 <*translations>
```

3.1 English Translations

```
645 <*english>
```

We provide the following English translations.

```
646 \ProvideDictionaryFor{English}{se2translations}[2024/02/22]
647 \ProvideDictTranslation{abstract}{abstract}
648 \ProvideDictTranslation{Abstract}{Abstract}
649 \ProvideDictTranslation{acknowledgement}{acknowledgement}
650 \ProvideDictTranslation{Acknowledgement}{Acknowledgement}
651 \ProvideDictTranslation{acknowledgements}{acknowledgements}
652 \ProvideDictTranslation{Acknowledgements}{Acknowledgements}
653 \ProvideDictTranslation{advisor}{advisor}
654 \ProvideDictTranslation{Advisor}{Advisor}
655 \ProvideDictTranslation{advisors}{advisors}
656 \ProvideDictTranslation{Advisors}{Advisors}
657 \ProvideDictTranslation{co-advisor}{co-advisor}
658 \ProvideDictTranslation{Co-advisor}{Co-advisor}
659 \ProvideDictTranslation{co-advisors}{co-advisors}
660 \ProvideDictTranslation{Co-advisors}{Co-advisors}
661 \ProvideDictTranslation{matrnumber}{matriculation number}
662 \ProvideDictTranslation{Matrnumber}{Matriculation number}
663 \ProvideDictTranslation{supervisor}{supervisor}
664 \ProvideDictTranslation{Supervisor}{Supervisor}
665 \ProvideDictTranslation{co-supervisor}{co-supervisor}
666 \ProvideDictTranslation{Co-supervisor}{Co-supervisor}
667 \ProvideDictTranslation{external}{external examiner}
668 \ProvideDictTranslation{External}{External Examiner}
669 \ProvideDictTranslation{degreeprogramme}{programme}
670 \ProvideDictTranslation{Degreeprogramme}{Programme}
671 \ProvideDictTranslation{Bachelor-thesis}{Bachelor Thesis}
672 \ProvideDictTranslation{Bachelor-thesis-proposal}{Bachelor Thesis Proposal}
673 \ProvideDictTranslation{Master-thesis}{Master Thesis}
674 \ProvideDictTranslation{Master-thesis-proposal}{Master Thesis Proposal}
675 \ProvideDictTranslation{PhD-thesis}{PhD Thesis}
676 \ProvideDictTranslation{PhD-thesis-proposal}{PhD Thesis Proposal}
677 \ProvideDictTranslation{date}{date}
678 \ProvideDictTranslation{Date}{Date}
679 \ProvideDictTranslation{university-of-passau}{University of Passau}
```

```

680 \ProvideDictTranslation{up}{University of Passau}
681 \ProvideDictTranslation{fim}{Faculty of Computer Science and Mathematics}
682 </english>

```

3.2 German Translations

```

683 <*german>
    We provide the following German translations.
684 \ProvideDictionaryFor{German}{se2translations}[2024/02/22]
685 \ProvideDictTranslation{abstract}{Zusammenfassung}
686 \ProvideDictTranslation{Abstract}{Zusammenfassung}
687 \ProvideDictTranslation{acknowledgement}{Danksagung}
688 \ProvideDictTranslation{Acknowledgement}{Danksagung}
689 \ProvideDictTranslation{acknowledgements}{Danksagungen}
690 \ProvideDictTranslation{Acknowledgements}{Danksagungen}
691 \ProvideDictTranslation{advisor}{Betreuer}
692 \ProvideDictTranslation{Advisor}{Betreuer}
693 \ProvideDictTranslation{advisors}{Betreuer}
694 \ProvideDictTranslation{Advisors}{Betreuer}
695 \ProvideDictTranslation{co-advisor}{Mitbetreuer}
696 \ProvideDictTranslation{Co-advisor}{Mitbetreuer}
697 \ProvideDictTranslation{co-advisors}{Mitbetreuer}
698 \ProvideDictTranslation{Co-advisors}{Mitbetreuer}
699 \ProvideDictTranslation{matrnumber}{Matrikelnummer}
700 \ProvideDictTranslation{Matrnumber}{Matrikelnummer}
701 \ProvideDictTranslation{supervisor}{Prüfer}
702 \ProvideDictTranslation{Supervisor}{Prüfer}
703 \ProvideDictTranslation{co-supervisor}{Zweitprüfer}
704 \ProvideDictTranslation{Co-supervisor}{Zweitprüfer}
705 \ProvideDictTranslation{external}{Externer Gutachter}
706 \ProvideDictTranslation{External}{Externer Gutachter}
707 \ProvideDictTranslation{degreeprogramme}{Studiengang}
708 \ProvideDictTranslation{Degreeprogramme}{Studiengang}
709 \ProvideDictTranslation{Bachelor-thesis}{Bachelorarbeit}
710 \ProvideDictTranslation{Bachelor-thesis-proposal}{Bachelorarbeitsproposal}
711 \ProvideDictTranslation{Master-thesis}{Masterarbeit}
712 \ProvideDictTranslation{Master-thesis-proposal}{Masterarbeitsproposal}
713 \ProvideDictTranslation{PhD-thesis}{Dissertation}
714 \ProvideDictTranslation{PhD-thesis-proposal}{Dissertationsproposal}
715 \ProvideDictTranslation{date}{Datum}
716 \ProvideDictTranslation{Date}{Datum}
717 \ProvideDictTranslation{university-of-passau}{Universität Passau}
718 \ProvideDictTranslation{up}{Universität Passau}
719 \ProvideDictTranslation{fim}{Fakultät für Informatik und Mathematik}
720 </german>
721 </translations>

```

4 se2colors implementation

Start the DocStrip guards.

```
722 <*package>
```

Identify the internal prefix (L^AT_EX3 DocStrip convention): only internal material in this *submodule* should be used directly.

```
723 <@@=slcd_colors>
```

Identify the package and give the overall version information.

```
724 \ProvidesExplPackage {se2colors} {2024-02-22} {3.3.0}
```

```
725 {A colour support package for the se2thesis bundle}
```

4.1 Load-time options

`\l__slcd_colors_colormode_tl` Holds the colour mode selected by the user as a package load-time option.

```
726 \keys_define:nn { seiicolors }
727 {
728   cmode .choice:,
729   cmode / 4C .code:n = {
730     \PassOptionsToPackage{cmyk}{xcolor}
731     \tl_gset:Nn \l__slcd_colors_colormode_tl {4C}
732   },
733   cmode / RGB .code:n = {
734     \PassOptionsToPackage{rgb}{xcolor}
735     \tl_gset:Nn \l__slcd_colors_colormode_tl {RGB}
736   },
737   cmode / BW .code:n = {
738     \PassOptionsToPackage{gray}{xcolor}
739     \tl_gset:Nn \l__slcd_colors_colormode_tl {BW}
740   },
741   cmode / CMYK .meta:n = {cmode=4C},
742   cmode / cmyk .meta:n = {cmode=4C},
743   cmode / rgb .meta:n = {cmode=RGB},
744   cmode / gray .meta:n = {cmode=BW},
745   RGB .meta:n = {cmode=RGB},
746   rgb .meta:n = {cmode=RGB},
747   CMYK .meta:n = {cmode=4C},
748   cmyk .meta:n = {cmode=4C},
749   gray .meta:n = {cmode=BW},
750 }
751 \keys_set:nn { seiicolors } { cmode = 4C }
```

(End of definition for \l__slcd_colors_colormode_tl.)

4.2 Option handling

```
752 \IfFormatAtLeastTF { 2022-06-01 }
753 { \ProcessKeyOptions [ seiicolors ] }
754 {
755   \RequirePackage { l3keys2e }
756   \ProcessKeysOptions { seiicolors }
757 }
```

4.3 Colour definitions

Load the xcolor package for colour definitions.

```
758 \RequirePackage{xcolor}
```

Define the primary colours gray and orange as given by the University of Passau's style guides.

```
759 \definecolorset[named]{RGB/cmyk}{UPSE2-}{}{%
760 Orange,242,148,0/0.00,0.44,0.95,0.01;%
761 Gray,153,159,158/0.40,0.28,0.28,0.00;%
762 JUR,229,49,56/0.01,0.90,0.81,0.01;%
763 WIWI,0,96,57/0.87,0.20,0.87,0.36;%
764 PHIL,188,42,51/0.06,0.93,0.81,0.11;%
765 FIM,0,90,161/0.93,0.63,0.01,0.02;%
766 DarkGray,77,77,77/0.74,0.67,0.62,0.18;%
767 White,255,255,255/0.00,0.00,0.00,0.00;%
768 MediumGray,127,127,127/0.52,0.43,0.40,0.02;%
769 LightGray,229,229,229/0.08,0.06,0.04,0.00;%
770 LightRed,229,49,56/0.01,0.90,0.81,0.01;%
771 DarkRed,188,42,51/0.06,0.93,0.80,0.11;%
772 Green,0,96,57/0.87,0.20,0.86,0.35;%
773 Blue,0,90,161/0.93,0.63,0.01,0.02;%
774 AccentGray,153,159,158/0.40,0.28,0.28,0.00%
775 }
```

Define the derived colours.

```
776 \colorlet{UPSE2-DarkGray1}{UPSE2-DarkGray!20!white}
777 \colorlet{UPSE2-DarkGray2}{UPSE2-DarkGray!40!white}
778 \colorlet{UPSE2-DarkGray3}{UPSE2-DarkGray!60!white}
779 \colorlet{UPSE2-DarkGray4}{UPSE2-DarkGray!75!black}
780 \colorlet{UPSE2-DarkGray5}{UPSE2-DarkGray!50!black}
781 \colorlet{UPSE2-White1}{UPSE2-White!95!black}
782 \colorlet{UPSE2-White2}{UPSE2-White!85!black}
783 \colorlet{UPSE2-White3}{UPSE2-White!75!black}
784 \colorlet{UPSE2-White4}{UPSE2-White!65!black}
785 \colorlet{UPSE2-White5}{UPSE2-White!50!black}
786 \colorlet{UPSE2-MediumGray1}{UPSE2-MediumGray!20!white}
787 \colorlet{UPSE2-MediumGray2}{UPSE2-MediumGray!40!white}
788 \colorlet{UPSE2-MediumGray3}{UPSE2-MediumGray!60!white}
789 \colorlet{UPSE2-MediumGray4}{UPSE2-MediumGray!75!black}
790 \colorlet{UPSE2-MediumGray5}{UPSE2-MediumGray!50!black}
791 \colorlet{UPSE2-LightGray1}{UPSE2-LightGray!90!black}
792 \colorlet{UPSE2-LightGray2}{UPSE2-LightGray!75!black}
793 \colorlet{UPSE2-LightGray3}{UPSE2-LightGray!55!black}
794 \colorlet{UPSE2-LightGray4}{UPSE2-LightGray!25!black}
795 \colorlet{UPSE2-LightGray5}{UPSE2-LightGray!10!black}
796 \colorlet{UPSE2-Orange1}{UPSE2-Orange!20!white}
797 \colorlet{UPSE2-Orange2}{UPSE2-Orange!40!white}
798 \colorlet{UPSE2-Orange3}{UPSE2-Orange!60!white}
799 \colorlet{UPSE2-Orange4}{UPSE2-Orange!75!black}
800 \colorlet{UPSE2-Orange5}{UPSE2-Orange!50!black}
801 \colorlet{UPSE2-LightRed1}{UPSE2-LightRed!20!white}
802 \colorlet{UPSE2-LightRed2}{UPSE2-LightRed!40!white}
803 \colorlet{UPSE2-LightRed3}{UPSE2-LightRed!60!white}
804 \colorlet{UPSE2-LightRed4}{UPSE2-LightRed!75!black}
```

```

805 \colorlet{UPSE2-LightRed5}{UPSE2-LightRed!50!black}
806 \colorlet{UPSE2-DarkRed1}{UPSE2-DarkRed!20!white}
807 \colorlet{UPSE2-DarkRed2}{UPSE2-DarkRed!40!white}
808 \colorlet{UPSE2-DarkRed3}{UPSE2-DarkRed!60!white}
809 \colorlet{UPSE2-DarkRed4}{UPSE2-DarkRed!75!black}
810 \colorlet{UPSE2-DarkRed5}{UPSE2-DarkRed!50!black}
811 \colorlet{UPSE2-Green1}{UPSE2-Green!10!white}
812 \colorlet{UPSE2-Green2}{UPSE2-Green!25!white}
813 \colorlet{UPSE2-Green3}{UPSE2-Green!50!white}
814 \colorlet{UPSE2-Green4}{UPSE2-Green!75!white}
815 \colorlet{UPSE2-Green5}{UPSE2-Green!90!white}
816 \colorlet{UPSE2-Blue1}{UPSE2-Blue!20!white}
817 \colorlet{UPSE2-Blue2}{UPSE2-Blue!40!white}
818 \colorlet{UPSE2-Blue3}{UPSE2-Blue!60!white}
819 \colorlet{UPSE2-Blue4}{UPSE2-Blue!75!black}
820 \colorlet{UPSE2-Blue5}{UPSE2-Blue!50!black}
821 \colorlet{UPSE2-AccentGray1}{UPSE2-AccentGray!20!white}
822 \colorlet{UPSE2-AccentGray2}{UPSE2-AccentGray!40!white}
823 \colorlet{UPSE2-AccentGray3}{UPSE2-AccentGray!60!white}
824 \colorlet{UPSE2-AccentGray4}{UPSE2-AccentGray!75!black}
825 \colorlet{UPSE2-AccentGray5}{UPSE2-AccentGray!50!black}
826 </package>

```

5 se2fonts implementation

Start the DocStrip guards.

```
827 <*package>
```

Identify the internal prefix (L^AT_EX3 DocStrip convention): only internal material in this *submodule* should be used directly.

```
828 <@=slcd_fonts>
```

Identify the package and give the overall version information.

```
829 \ProvidesExplPackage {se2fonts} {2024-02-22} {3.3.0}
```

```
830 {A font-selection support package for the se2thesis bundle}
```

5.1 Load-time options

`\l__slcd_fonts_fontmode_tl` Holds the font-selection mode specified by the user as a package load-time option. *Please note: this option is deprecated!*

```
831 \tl_new:N \l__slcd_fonts_fontmode_tl
832 \keys_define:nn { seiifonts }
833 {
834   fmode .choice:,
835   fmode / original .code:n = {
836     \tl_gset:Nn \l__slcd_fonts_fontmode_tl {original}
837   },
838   fmode / replacement .code:n = {
839     \tl_gset:Nn \l__slcd_fonts_fontmode_tl {replacement}
840   },
841   fmode / auto .code:n = {
842     \tl_gset:Nn \l__slcd_fonts_fontmode_tl {auto}
843   },
844   original .meta:n = {fmode=original},
845   replacement .meta:n = {fmode=replacement},
846   auto .meta:n = {fmode=auto},
847 }
```

(End of definition for `\l__slcd_fonts_fontmode_tl`.)

5.2 Option handling

```
848 \IfFormatAtLeastTF { 2022-06-01 }
849 { \ProcessKeyOptions [ seiifonts ] }
850 {
851   \RequirePackage{ l3keys2e }
852   \ProcessKeysOptions { seiifonts }
853 }
```

Define a warning message

```
854 \msg_set:nnnn { seiifonts } { deprecated-option }
855 { The~ option~ fmode~ to~ the~ se2fonts~ package~ is~ deprecated. }
856 { Remove~ it~ from~ your~ code. }
```

Raise the warning if the option was used

```
857 \tl_if_empty:NF \l__slcd_fonts_fontmode_tl
858 {
859   \msg_warning:nn { seiifonts } { deprecated-option }
```



```
860 }
```

5.3 Helper macros

`\pdfxengine` We define several alias macros to identify which engine the user is running.

```
\xetengine 861 \cs_new_eq:NN \pdfxengine \sys_if_engine_pdfx_p:
\luatengine 862 \cs_new_eq:NN \xetengine \sys_if_engine_xetex_p:
863 \cs_new_eq:NN \luatengine \sys_if_engine_luatex_p:
```

(End of definition for `\pdfxengine`, `\xetengine`, and `\luatengine`. These functions are documented on page 9.)

`\ifengineTF` True, if the engine used matches the given first argument.

```
\ifengineT 864 \NewExpandableDocumentCommand \ifengineTF { mmm }
\ifengineF 865 {
866   \bool_if:nTF { #1 } { #2 } { #3 }
867 }
868 \NewExpandableDocumentCommand \ifengineT { mm }
869 {
870   \bool_if:nT { #1 } { #2 }
871 }
872 \NewExpandableDocumentCommand \ifengineF { mm }
873 {
874   \bool_if:nF { #1 } { #2 }
875 }
```

(End of definition for `\ifengineTF`, `\ifengineT`, and `\ifengineF`. These functions are documented on page 9.)

The package is not tested with Xe_{La}TeX, thus we provide an error to the user and stop the execution if they want to use the package with Xe_{La}TeX.

```
876 \ifengineT { \xetengine }
877 {
878   \msg_set:nnnn { seiifonts } { xetex-not-supported }
879   { XeTeX is not supported by the se2fonts package. }
880   { Switch to pdfTeX or (preferably) LuaTeX. }
881   \msg_error:nn { seiifonts } { xetex-not-supported }
882 }
```

5.4 Font loading

Depending on the engine used by the user, we can use fontspec for loading fonts.

```
883 \ifengineTF { \luatengine }
884 {
885   If the user uses LuaTeX, load fontspec and unicode-math.
886   \RequirePackage{fontspec}
887   \RequirePackage{unicode-math}
```

To make sure the scaling of the fonts matches, we let fontspec do this matching based on the lower-case characters.

```
888   \defaultfontfeatures{ Scale = MatchLowercase }
889   \defaultfontfeatures[\rmfamily]{ Scale = 1 }
890   Load the respective libertine-otf package and omit the monospaced font.
891   \PassOptionsToPackage{mono=false}{libertinus-otf}
892   \RequirePackage{libertinus-otf}
```

Load the *Inconsolata Nerd Font* monospaced font.

```
891 \RequirePackage{inconsolata-nerd-font}
892 } {
    The user does not use Lua $\TeX$ , thus fallback to T1 fonts.
893 \PassOptionsToPackage{T1}{fontenc}
894 \PassOptionsToPackage{scaled=0.9,varl}{inconsolata}
895 \PassOptionsToPackage{mono=false}{libertinus-type1}
896 \RequirePackage{fontenc}
897 \RequirePackage{inconsolata}
898 \RequirePackage{libertinus-type1}
899 }
900 </package>
```

6 se2packages implementation

Start the DocStrip guards.

```
901 <*package>
```

Identify the internal prefix (L^AT_EX3 DocStrip convention): only internal material in this *submodule* should be used directly.

```
902 <@=slcd_packages>
```

Identify the package and give the overall version information.

```
903 \ProvidesExplPackage {se2packages} {2024-02-22} {3.3.0}
```

```
904 {Supporting packages for the se2thesis bundle}
```

6.1 Load-time options

Before we define the actual options, define some Boolean variables to store the selected values.

```
\l_slcd_packages_csquotes_bool Whether or not to load csquotes.  
905 \bool_new:N \l_slcd_packages_csquotes_bool  
(End of definition for \l_slcd_packages_csquotes_bool.)
```

```
\l_slcd_packages_booktabs_bool Whether or not to load booktabs.  
906 \bool_new:N \l_slcd_packages_booktabs_bool  
(End of definition for \l_slcd_packages_booktabs_bool.)
```

```
\l_slcd_packages_siunitx_bool Whether or not to load and configure siunitx.  
907 \bool_new:N \l_slcd_packages_siunitx_bool  
(End of definition for \l_slcd_packages_siunitx_bool.)
```

```
\l_slcd_packages_minted_bool Whether or not to load and configure minted.  
908 \bool_new:N \l_slcd_packages_minted_bool  
(End of definition for \l_slcd_packages_minted_bool.)
```

```
\l_slcd_packages_listings_bool Whether or not to load and configure listings.  
909 \bool_new:N \l_slcd_packages_listings_bool  
(End of definition for \l_slcd_packages_listings_bool.)
```

```
\l_slcd_packages_biblatex_tl Whether or not to load and configure biblatex.  
910 \tl_new:N \l_slcd_packages_biblatex_tl  
(End of definition for \l_slcd_packages_biblatex_tl.)
```

```
\l_slcd_packages_selnolig_bool Whether or not to load selnolig (LuaTEX only).  
911 \bool_new:N \l_slcd_packages_selnolig_bool  
(End of definition for \l_slcd_packages_selnolig_bool.)
```

```
\l_slcd_packages_luawindowcontrol_bool Whether or not to load luawindowcontrol (LuaTEX only).  
912 \bool_new:N \l_slcd_packages_luawindowcontrol_bool  
(End of definition for \l_slcd_packages_luawindowcontrol_bool.)
```

```

\l_slcd_packages_microtype_bool Whether or not to load microtype.
913 \bool_new:N \l_slcd_packages_microtype_bool
(End of definition for \l_slcd_packages_microtype_bool.)

\l_slcd_packages_cleveref_bool Whether or not to load and configure cleveref.
914 \bool_new:N \l_slcd_packages_cleveref_bool
(End of definition for \l_slcd_packages_cleveref_bool.)

\l_slcd_packages_all_bool Whether or not to load and configure all recommended packages.
915 \bool_new:N \l_slcd_packages_all_bool
(End of definition for \l_slcd_packages_all_bool.)
  Define the actual load-time options.
916 \keys_define:nn { seiipackages }
917 {
918   csquotes .bool_gset:N = \l_slcd_packages_csquotes_bool,
919   csquotes .initial:n = true,
920   nocsthrough .meta:n = {csquotes=false},
921
922   booktabs .bool_gset:N = \l_slcd_packages_booktabs_bool,
923   booktabs .initial:n = true,
924   nobooktabs .meta:n = {booktabs=false},
925
926   siunitx .bool_gset:N = \l_slcd_packages_siunitx_bool,
927   siunitx .initial:n = false,
928
929   minted .bool_gset:N = \l_slcd_packages_minted_bool,
930   minted .initial:n = false,
931
932   listings .bool_gset:N = \l_slcd_packages_listings_bool,
933   listings .initial:n = false,
934
935   biblatex .tl_gset:N = \l_slcd_packages_biblatex_tl,
936   biblatex .initial:n = false,
937
938   selnolig .bool_gset:N = \l_slcd_packages_selnolig_bool,
939   selnolig .initial:n = true,
940   noselnolig .meta:n = {selnolig=false},
941
942   widowcontrol .bool_gset:N = \l_slcd_packages_luawidowcontrol_bool,
943   widowcontrol .initial:n = false,
944   nowidowcontrol .meta:n = {widowcontrol=false},
945
946   microtype .bool_gset:N = \l_slcd_packages_microtype_bool,
947   microtype .initial:n = true,
948   nomicrotype .meta:n = {microtype=false},
949
950   cleveref .bool_gset:N = \l_slcd_packages_cleveref_bool,
951   cleveref .initial:n = false,
952
953   all .bool_gset:N = \l_slcd_packages_all_bool,
954   all .initial:n = false,
955 }

```

6.2 Option handling

```
956 \IfFormatAtLeastTF { 2022-06-01 }
957 { \ProcessKeyOptions [ seiipackages ] }
958 {
959   \RequirePackage{ l3keys2e }
960   \ProcessKeysOptions { seiipackages }
961 }
```

Define an error message if both minted and listings are requested.

```
962 \msg_set:nnnn { seiipackages } { conflicting-packages }
963 { Setting~ both~ minted~ and~ listings~ to~ true~ is~ not~ possible. }
964 { Choose~ either~ of~ them! }
```

Define a message for logging that a specific package will be loaded by se2packages. Expects as parameter the name of the package that will be loaded.

```
965 \msg_new:nnn { seiipackages } { load-package }
966 { se2packages~ loads~ the~ #1~ package now. }
```

And, in case both values are set to true, raise the error message.

```
967 \bool_lazy_and:nnT { \l__slcd_packages_minted_bool } { \l__slcd_packages_listings_bool }
968 {
969   \msg_error:nn { seiipackages } { conflicting-packages }
970 }
```

In case the all option is set, set all other values to true.

```
971 \bool_if:NT \l__slcd_packages_all_bool
972 {
973   \bool_gset_true:N \l__slcd_packages_csquotes_bool
974   \bool_gset_true:N \l__slcd_packages_booktabs_bool
975   \bool_gset_true:N \l__slcd_packages_siunitx_bool
976   \bool_gset_true:N \l__slcd_packages_minted_bool
977   \bool_gset_false:N \l__slcd_packages_listings_bool
978   \bool_gset_true:N \l__slcd_packages_selnolig_bool
979   \bool_gset_true:N \l__slcd_packages_luawindowcontrol_bool
980   \bool_gset_true:N \l__slcd_packages_microtype_bool
981   \tl_gset:Nn \l__slcd_packages_biblatex_bool {true}
982   \bool_gset_true:N \l__slcd_packages_cleveref_bool
983 }
```

6.3 Package loading

Conditionally load the csquotes package.

```
984 \bool_if:NT \l__slcd_packages_csquotes_bool
985 {
986   \msg_info:nnn { seiipackages } { load-package } { csquotes }
987   \RequirePackage{fvextra}
988   \RequirePackage{csquotes}
989 }
```

Conditionally load the booktabs package.

```
990 \bool_if:NT \l__slcd_packages_booktabs_bool
991 {
992   \msg_info:nnn { seiipackages } { load-package } { booktabs }
993   \RequirePackage{booktabs}
994 }
```

Conditionally load and configure the siunitx package.

```
995 \bool_if:NT \l__slcd_packages_siunitx_bool
996 {
997   \msg_info:nnn { seiipackages } { load-package } { siunitx }
998   \RequirePackage[
999     add-integer-zero=false,
1000     free-standing-units,
1001     group-minimum-digits=4,
1002     list-final-separator={, and },
1003     round-mode=figures,
1004     round-precision=3,
1005     separate-uncertainty=true,
1006     uncertainty-mode=separate,
1007   ]{siunitx}
1008 }
```

Conditionally load and configure the minted package.

```
1009 \bool_if:NT \l__slcd_packages_minted_bool
1010 {
1011   \msg_info:nnn { seiipackages } { load-package } { minted }
1012   \RequirePackage[newfloat=true]{minted}
1013   \setminted{
1014     autogobble,
1015     breaklines=true,
1016     fontsize=\footnotesize,
1017     frame=single,
1018     linenos=false,
1019     resetmargins=true,
1020     xleftmargin=1em,
1021     xrightmargin=1em,
1022   }
1023 }
```

Conditionally load and configure the listings package.

```
1024 \bool_if:NT \l__slcd_packages_listings_bool
1025 {
1026   \msg_info:nnn { seiipackages } { load-package } { listings }
1027   \RequirePackage{listings}
1028   \lstset{
1029     basicstyle=\footnotesize\ttfamily,
1030     breaklines=true,
1031     captionpos=t,
1032     extendedchars=true,
1033     frame=single,
1034     keywordstyle=\color{blue}\bfseries,
1035     showspaces=false,
1036     showtabs=false,
1037     showstringspaces=false,
1038     tabsize=2,
1039   }
1040 }
```

Conditionally load selnolig if present and we run Lua \TeX .

```
1041 \bool_lazy_and:nnT { \l__slcd_packages_selnolig_bool } { \sys_if_engine luatex_p: }
1042 {
```

```

1043 \IfFileExists { selnolig.sty }
1044 {
1045   \RequirePackage{selnolig}
1046 } {
1047   \msg:nnon { seiipackages }
1048   { selnolig-not-available }
1049   { Could~ not~ find~ selnolig.sty }
1050   { You~ might~ want~ to~ install~ it~ for~ better~ ligatures~ control.}
1051   \msg_note:nn { seiipackages } { selnolig-not-available }
1052 }
1053 }

```

Conditionally load luawidowcontrol if present and we run Lua \TeX .

```

1054 \bool_lazy_and:nnT { \l__slcd_packages_luawidowcontrol_bool } { \sys_if_engine luatex_p: }
1055 {
1056   \IfFileExists { lua-widow-control.sty }
1057   {
1058     \RequirePackage{lua-widow-control}
1059   } {
1060     \msg:nnon { seiipackages }
1061     { lua-widow-control-not-available }
1062     { Could~ not~ find~ lua-widow-control.sty }
1063     {
1064       You~ might~ want~ to~ install~ it~ for~ better~ control~ over~
1065       widows~ and~ orphans.
1066     }
1067     \msg_note:nn { seiipackages } { lua-widow-control-not-available }
1068   }
1069 }

```

Conditionally load and configure microtype. If a package option requires for the lua-widow-control package, we do not set penalties for widows and orphans but let that package control these penalties.

```

1070 \bool_if:NT \l__slcd_packages_microtype_bool
1071 {
1072   \msg_info:nnn { seiipackages } { load-package } { microtype }
1073   \RequirePackage{microtype}
1074   \bool_if:NF \l__slcd_packages_luawidowcontrol_bool
1075   {
1076     \clubpenalty=10000
1077     \widowpenalty=10000
1078     \displaywidowpenalty=10000
1079   }
1080   \SetExtraKerning{
1081     encoding = {OT1,T1,T2A,LY1,OT4,QX,T5,TS1,EU1,EU2}
1082   }{
1083     \textendash = {167,167},
1084     - = {167,167}
1085   }
1086 }

```

Conditionally load and configure the biblalex package.

```

1087 \tl_if_eq:NnT \l__slcd_packages_biblalex_tl {alphabetic}
1088 {
1089   \msg_info:nnn { seiipackages } { load-package } { biblalex }

```

```

1090 \PassOptionsToPackage
1091 {
1092     backend=biber,
1093     backref=true,
1094     datamodel=software,
1095     giveninits=true,
1096     hyperref=auto,
1097     maxnames=100,
1098     minalphames=3,
1099     sorting=nyt,
1100     style=alphabetic,
1101 } { biblatex }
1102 \RequirePackage{biblatex}
1103 \RequirePackage{software-biblatex}
1104 \ExecuteBibliographyOptions{
1105     halid=false,
1106     swhid=true,
1107     shortswid=false,
1108     swlabels=true,
1109     vcs=true,
1110     license=true,
1111 }
1112 }
1113
1114 \bool_new:N \l__slcd_packages_biblatex_numeric_variants_bool
1115 \tl_if_eq:NnT \l__slcd_packages_biblatex_tl {true}
1116 {
1117     \bool_gset_true:N \l__slcd_packages_biblatex_numeric_variants_bool
1118 }
1119 \tl_if_eq:NnT \l__slcd_packages_biblatex_tl {numeric}
1120 {
1121     \bool_gset_true:N \l__slcd_packages_biblatex_numeric_variants_bool
1122 }
1123
1124 \bool_if:NT \l__slcd_packages_biblatex_numeric_variants_bool
1125 {
1126     \msg_info:nnn { seiipackages } { load-package } { biblatex }
1127     \PassOptionsToPackage
1128     {
1129         backend=biber,
1130         backref=true,
1131         citereset=chapter+,
1132         citetracker=context,
1133         giveninits=true,
1134         hyperref=auto,
1135         sorting=nyt,
1136         datamodel=acmdatamodel,
1137         style=acmnumeric,
1138     } { biblatex }
1139     \RequirePackage{biblatex}
1140     \RequirePackage{ragged2e}
1141     \RequirePackage[mark=arabic,shape=up]{sidenotesplus}
1142
1143     \newbibmacro{cite:authoryear}{%

```



```

1144     \printtext[labelnumberwidth]{%
1145       \usebibmacro{cite}%
1146     }%
1147     \setunit{\addspace}%
1148     \printnames{labelname}%
1149     \setunit{\printdelim{nameyeardelim}}%
1150     \begingroup
1151     \DeclareFieldFormat{date}{\mkbibparens{##1}}%
1152     \printdate
1153     \endgroup
1154     \setunit*{\addcomma\space}%% NEW
1155     \printfield[title]{labeltitle}%% NEW
1156   }
1157
1158   \newrobustcmd*{\makebibmarginnote}[1]{%
1159     \sidenote*{\blxmkbibnote{foot}{#1}}}
1160
1161   \DeclareCiteCommand{\maycite}[\makebibmarginnote]
1162     {\usebibmacro{prenote}}
1163     {\usebibmacro{citeindex}%
1164       \usebibmacro{cite:authoryear}}
1165     {\multicitedelim}
1166     {\usebibmacro{postnote}}
1167
1168   \newcommand*{\cbx@savetcites}{}
1169
1170   \newcommand*{\cbx@margcitewrap}[1]{%
1171     \global\let\cbx@savetcites\empty
1172     \mkbibbrackets{#1}%
1173     \cbx@savetcites
1174   }
1175
1176   \DeclareCiteCommand{\margincite}[\cbx@margcitewrap]
1177     {\usebibmacro{prenote}}
1178     {\usebibmacro{citeindex}%
1179       \usebibmacro{cite}%
1180       \ifciteseen
1181         {}
1182         {\xappto\cbx@savetcites{\noexpand\maycite{\thefield{entrykey}}}}
1183     {\multicitedelim}
1184     {\usebibmacro{postnote}}
1185
1186   \DeclareMultiCiteCommand{\margincites}[\cbx@margcitewrap]{\margincite}{\multicitedelim}
1187
1188   \DeclareAutoCiteCommand{margin}{\margincite}{\margincites}
1189   \ExecuteBibliographyOptions{autocite=margin}
1190   \newcommand{\bibliofoot}{\footnotesize}
1191   \DeclareFieldFormat{titlecase}{#1}% Preserve capitalisation of titles
1192 }

```

Conditionally load the cleveref package as the last of the preamble.

```

1193 \bool_if:NT \l__slcd_packages_cleveref_bool
1194 {
1195   \msg_info:nnn { seiipackages } { load-package } { cleveref }
1196   \AddToHook { begindocument/before }

```

```

1197     {
1198     \RequirePackage[capitalise]{cleveref}
1199     }
1200 }
1201 </package>

```

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols	
<code>\&</code>	300
<code>\,</code>	404
<code>\ </code>	403, 404, 405, 406, 407, 408, 409, 410, 411, 416, 417, 418, 419, 420, 421, 422, 423, 424, 451, 455, 459, 463, 467, 471, 488, 489, 623, 628
<code>\ _</code>	33, 36, 39, 225, 238, 439
A	
<code>abstract (env.)</code>	5, <u>527</u>
<code>\abstract</code>	5, 29, <u>526</u>
<code>acknowledgements (env.)</code>	5, <u>544</u>
<code>\addcomma</code>	1154
<code>\addspace</code>	1147
<code>\AddtoDoHook</code>	523
<code>\AddToHook</code>	1196
<code>\addtokomafont</code>	499, 500, 501, <u>502</u>
<code>\advisor</code>	4, <u>163</u>
<code>all</code>	13
<code>\and</code>	4, 292
<code>\areaset</code>	212, 216
<code>\author</code>	3, 4, 6, 20, <u>290</u>
<code>\authorshipDeclaration</code>	6, <u>578</u>
<code>\autocite</code>	13
<code>\autodot</code>	505
B	
<code>\backmatter</code>	5, <u>567</u>
<code>\baselineskip</code>	336, <u>513</u>
<code>\begin</code>	233, 249, 257, 269, 316, 352, 356, 400, 447, 448, 609, 641
<code>\beginngroup</code>	327, 1150
<code>\bfseries</code>	499, 1034
<code>biblatex</code>	13
<code>\bibliofont</code>	1190
<code>\bigskip</code>	393, 397, 446, 510, 619
<code>\blxmkbibnote</code>	1159
<code>booktabs</code>	12
bool commands:	
<code>\bool_gset_false:N</code>	977
<code>\bool_gset_true:N</code>	973, 974, 975, 976, 978, 979, 980, 982, 1117, 1121
<code>\bool_if:NTF</code>	971, 984, 990, 995, 1009, 1024, 1070, 1074, 1124, 1193
<code>\bool_if:nTF</code>	866, 870, 874
<code>\bool_lazy_and:nnTF</code>	967, 1041, 1054
<code>\bool_new:N</code>	905, 906, 907, 908, 909, 911, 912, 913, 914, 915, 1114
<code>\bottomrule</code>	11
box commands:	
<code>\box_ht:N</code>	310, 378, 380
<code>\box_if_exist:NTF</code>	197, 365
<code>\box_new:N</code>	199, 367
<code>\box_use:N</code>	311, 379
<code>\box_wd:N</code>	309
C	
<code>\caption</code>	11
<code>\centering</code>	388, 391, 395, 478, 627
<code>\chapter</code>	539, 555, 605
<code>\chapterformat</code>	503
<code>\chapterlinesformat</code>	508
<code>\chapterlineswithprefixformat</code>	514
<code>class</code>	2
<code>\cleardoubleoddpaper</code>	563, 569, 575
<code>\cleardoublepage</code>	623
<code>\clearpage</code>	362, 536, 563, 569, 575
<code>\clearpairofpagestyles</code>	222
<code>cleveref</code>	13
clist commands:	
<code>\clist_map_inline:nn</code>	125
<code>\clubpenalty</code>	1076
<code>cmode</code>	7
<code>\coadvisor</code>	4, <u>163</u>
<code>\color</code>	229, 241, 245, 263, 275, 280, 505, 1034
<code>\colorlet</code>	776, 777, 778, 779, 780, 781, 782, 783, 784, 785, 786, 787, 788, 789, 790, 791, 792,

793, 794, 795, 796, 797, 798, 799, 800, 801, 802, 803, 804, 805, 806, 807, 808, 809, 810, 811, 812, 813, 814, 815, 816, 817, 818, 819, 820, 821, 822, 823, 824, 825	
colormode	3
\columnwidth	340
\cosupervisor	4, 155
\coverpagebottommargin	333
\coverpagetopmargin	308, 328, 333
cs commands:	
\cs_if_exist:NTF	132
\cs_new:Nn	385
\cs_new_eq:NN	861, 862, 863
csquotes	12
D	
\DeclareAutoCiteCommand	1188
\DeclareCiteCommand	1161, 1176
\DeclareFieldFormat	1151, 1191
\DeclareMultiCiteCommand	1186
\DeclareNewLayer	303
\DeclareNewPageStyleByLayers	313
\DeclareTranslation	35, 38
\DeclareTranslationFallback	32
\def	318
\defaultfontfeatures	887, 888
\definecolorset	759
\degreeprogramme	3, 26, 147
\department	4, 26, 171
\dictumwidth	525
dim commands:	
\dim_gset:Nn	65, 66, 67, 68, 69, 70, 71, 192, 194
\dim_if_exist:NTF	187
\dim_new:N	58, 59, 60, 61, 62, 63, 64, 189
\dimexpr	328, 329, 330, 331, 332
\displaywidowpenalty	1078
E	
\edef	319
\else	362, 390, 563, 569, 575
\emph	489
\empty	1171
\end	235, 251, 259, 271, 354, 358, 363, 446, 473, 474, 618, 642
\endgroup	320, 1153
\endinput	14
\enskip	504
environments:	
abstract	5, 527
acknowledgements	5, 544
hyp	6, 637
resq	6, 637
summary	6, 640
\evensidemargin	330
\ExecuteBibliographyOptions	1104, 1189
exp commands:	
\exp_args:NV	398
\ExplFileDate	16
\ExplLoaderFileDate	5
\external	4, 179
F	
\fi	360, 361, 362, 392, 563, 569, 575
\fmtversion	16
\fnsymbol	318
\footnotesize	226, 239, 256, 260, 268, 272, 1016, 1029, 1190
\footskip	336
\frontmatter	5, 561
G	
\GetTranslation	300, 428, 430, 432, 434, 436, 451, 455, 459, 463, 467, 471, 481, 491, 493, 495, 496, 540, 556
\global	321, 322, 323, 324, 1171
group commands:	
\group_begin:	225, 228, 238, 240, 244, 262, 274, 279, 298, 370, 387, 394, 476, 487, 529, 546, 581
\group_end:	225, 231, 238, 242, 247, 265, 277, 281, 301, 381, 389, 396, 483, 497, 542, 558, 622
H	
hbox commands:	
\hbox_gset:Nn	203, 373
\headheight	334
\headingdot	523, 524
\headmark	241, 280
\headsep	335
\hfill	620
\hline	10
\hrule	511
\hrulefill	509
\hspace	341, 342
\hspace	227, 232, 236, 243, 248, 252, 255, 261, 267, 273, 278
\ht	308
\Huge	284
hyp (env.)	6, 637
\hyphenpenalty	299
I	
\ifciteseen	1180
\ifengineF	9, 864
\ifengineT	9, 864 , 876
\ifengineTF	9, 864 , 883
\IfFileExists	1043, 1056
\IfFormatAtLeastTF	2, 16 , 114, 752, 848, 956

<code>\IfNoValueF</code>	530, 547, 583	<code>\midrule</code>	11
<code>\Ifstr</code>	515	<code>minted</code>	12
<code>\Iftocfeature</code>	532, 537, 549, 553, 599, 603	<code>\mkbibbrackets</code>	1172
<code>\ifx</code>	362, 390	<code>\mkbibparens</code>	1151
<code>\includegraphics</code>	205	msg commands:	
<code>\institute</code>	4, 26, <u>171</u>	<code>\msg:nnnn</code>	1047, 1060
int commands:		<code>\msg_error:nn</code>	881, 969
<code>\int_compare:nTF</code>	190, 210	<code>\msg_info:nnn</code>	986,
<code>\int_gset_eq:NN</code>	82	992, 997, 1011, 1026, 1072, 1089, 1126, 1195	
<code>\int_new:N</code>	41	<code>\msg_new:nnn</code>	588, 965
<code>\item</code>	610, 615	<code>\msg_note:nn</code>	1051, 1067
<code>\itshape</code>	522	<code>\msg_set:nnnn</code>	854, 878, 962
		<code>\msg_warning:nn</code>	595, 859
		<code>\multicitedelim</code>	1165, 1183, 1186
		N	
K		<code>\newbibmacro</code>	1143
keys commands:		<code>\newcommand</code>	524, 625, 1168, 1170, 1190
<code>\l_keys_choice_int</code>	82	<code>\NewDocumentCommand</code>	578
<code>\l_keys_choice_tl</code>	106	<code>\NewDocumentEnvironment</code>	544, 640
<code>\keys_define:nn</code>	72, 726, 832, 916	<code>\NewExpandableDocumentCommand</code> ...	864, 868, 872
<code>\l_keys_key_tl</code>	111	<code>\newif</code>	560
<code>\keys_set:nn</code>	751	<code>\newrobustcmd</code>	1158
<code>\KOMAOption</code>	136	<code>\newtheorem</code>	31, 637, 638
<code>\KOMAOptions</code>	135	<code>nobooktabs</code>	12
		<code>nocsquotes</code>	12
		<code>\noexpand</code>	320, 321, 322, 323, 324, 325, 1182
		<code>\noindent</code>	488, 620
L		<code>nomicrotype</code>	13
<code>\label</code>	11	<code>\normalfont</code>	223, 522
<code>\Large</code>	285	<code>\normalsize</code>	
<code>\large</code>	287, 501	234, 250, 258, 270, 286, 288, 289, 502, 522	
<code>\leftfoot</code>	254	<code>nosel nolig</code>	12
<code>\let</code>	325, 359, 382, 536, 1171	<code>nowidowcontrol</code>	12
<code>\linewidth</code>	342, 525, 628	<code>\null</code>	255, 267, 377
<code>listings</code>	12	<code>\num</code>	10
<code>\LoadClass</code>	129		
<code>\LoadDictionary</code>	31	O	
<code>\location</code>	4, 6, <u>183</u>	<code>\oddsidemargin</code>	307, 329
<code>logfile</code>	3		
<code>\lstset</code>	1028	P	
<code>\luatexengine</code>	9, <u>861</u> , 883	<code>\PackageError</code>	8
		<code>\pagemark</code>	234, 250, 258, 270
M		<code>\pagenumbering</code>	565, 571
<code>\mainmatter</code>	5, <u>567</u>	<code>\pagestyle</code>	283
<code>\makebibmarginnote</code>	1158, 1161	<code>paper</code>	3
<code>\makebox</code>	628	<code>\paperheight</code>	333
<code>\maketitle</code>	3, 24, 315	<code>\paperwidth</code>	331
<code>\MakeUppercase</code>	516, 520	<code>\par</code>	358, 388, 391, 395, 441,
<code>\margincite</code>	1176, 1186, 1188	442, 443, 446, 475, 482, 509, 510, 580, 618	
<code>\margincites</code>	1186, 1188	<code>\paragraph</code>	28
<code>\marginparsep</code>	213, 214, 217, 218	<code>\parbox</code>	375, 509, 626
<code>\matrnumber</code>	3, <u>151</u>	<code>\PassOptionsToClass</code>	123, 126
<code>\maycite</code>	1161, 1182	<code>\PassOptionsToPackage</code>	139, 220, 633,
<code>\mbox</code>	504	730, 734, 738, 889, 893, 894, 895, 1090, 1127	
<code>\mdseries</code>	500, 501, 502		
<code>\medskip</code>	391, 475		
<code>\MessageBreak</code>	11		
<code>microtype</code>	13		

\pdftexengine	9, 861	S	
prg commands:		\scalebox	505
\prg_new_conditional:Nnn	22	\section	534, 538, 551, 554, 601, 604
\prg_return_false:	27	\sectionlinesformat	519
\prg_return_true:	26	\selectlanguage	530, 547, 582
\printdate	1152	selnolig	12
\printdelim	1149	seq commands:	
\printfield	1155	\seq_gset_split:Nnn	292
\printnames	1148	\seq_new:N	290
\printtext	1144	\seq_use:Nnnn	300
\ProcessKeyOptions	115, 753, 849, 957	\setcounter	317
\ProcessKeysOptions	118, 756, 852, 960	\SetExtraKerning	1080
prop commands:		\setkomafont	223, 284, 285, 286, 287, 288, 289, 522
\prop_gput:Nnn	111	\setlength	213, 214, 217, 218
\prop_map_inline:Nn	120, 130	\setminted	1013
\prop_new:N	43, 44	\setparsizes	343, 371
\providecommand	16, 526, 561, 567, 573	\setunit	1147, 1149, 1154
\ProvideDictionaryFor	646, 684	\sffamily	223
\ProvideDictTranslation	647, 648, 649, 650, 651, 652, 653, 654, 655, 656, 657, 658, 659, 660, 661, 662, 663, 664, 665, 666, 667, 668, 669, 670, 671, 672, 673, 674, 675, 676, 677, 678, 679, 680, 681, 685, 686, 687, 688, 689, 690, 691, 692, 693, 694, 695, 696, 697, 698, 699, 700, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 711, 712, 713, 714, 715, 716, 717, 718, 719	\sidenote	1159
\ProvideDocumentCommand	143, 147, 151, 155, 159, 163, 167, 171, 175, 179, 183	\signatureBox	6, 621, 625
\ProvidesExplClass	20	siunitx	12
\ProvidesExplPackage	724, 829, 903	skip commands:	
\putUL	311	\skip_vertical:n	378, 380
		slcd commands:	
Q		\slcd_package_if_loaded:n	22
\qty	10	\slcd_package_if_loaded:nTF	2, 22 , 631
\quad	448	\slcd_package_if_loaded_p:n	2, 22
		slcd internal commands:	
R		\l__slcd_advisor_tl	45, 165, 461, 463
\raggedleft	258, 270, 499	\l__slcd_author_seq	290, 292, 300
\RedeclareSectionCommand	513	\l__slcd_base_class_tl	42, 72 , 123, 126, 129, 132
\ref	11	\l__slcd_clsopts_prop	42, 120
\relax	325, 328, 329, 330, 331, 333, 362, 536	\l__slcd_coadvisor_tl	45, 169, 465, 467
\renewcommand	291, 297, 314, 315, 369, 486, 503, 508, 514, 519, 525	\l__slcd_colormode_tl	72, 139
\RenewDocumentEnvironment	527	\l__slcd_colors_colormode_tl	726
\RequirePackage	3, 29, 30, 117, 140, 142, 221, 384, 635, 639, 755, 758, 851, 885, 886, 890, 891, 896, 897, 898, 959, 987, 988, 993, 998, 1012, 1027, 1045, 1058, 1073, 1102, 1103, 1139, 1140, 1141, 1198	\l__slcd_cosupervisor_tl	45, 161, 457, 459
resq (env.)	6, 637	\l__slcd_degreeprogramme_tl	45, 149, 437, 439
\rmfamily	888	\l__slcd_department_tl	45, 173, 442
\rofoot	224	\l__slcd_external_tl	45, 181, 469, 471
\rule	230, 246, 264, 276, 407, 420, 628	\l__slcd_fonts_fontmode_tl	831, 857
		\l__slcd_headmarkspace_dim	58, 227, 278
		\l__slcd_institute_tl	45, 177, 443
		\l__slcd_licensemodifier_tl	72
		\l__slcd_licensetype_tl	72
		\l__slcd_licenseversion_tl	72
		\l__slcd_location_tl	45, 185, 584, 586, 620
		\l__slcd_logo_box	187, 309, 310, 311, 378, 380
		\l__slcd_logo_height_dim	187
		\l__slcd_logofile_tl	45, 86, 201, 207
		\l__slcd_marginspace_dim	58, 236, 252, 255, 267
		\l__slcd_matrnumber_tl	45, 153, 449, 451
		\l__slcd_packages_all_bool	915, 953, 971
		\l__slcd_packages_biblatex_bool	981

`\l__slcd_packages_biblatex_numeric_variants_bool` 1114, 1117, 1121, 1124
`\l__slcd_packages_biblatex_tl`
. 910, 935, 1087, 1115, 1119
`\l__slcd_packages_booktabs_bool`
. 906, 922, 974, 990
`\l__slcd_packages_cleveref_bool`
. 914, 950, 982, 1193
`\l__slcd_packages_csquotes_bool`
. 905, 918, 973, 984
`\l__slcd_packages_listings_bool`
. 909, 932, 967, 977, 1024
`\l__slcd_packages_luawidowcontrol_bool`
. 912, 942, 979, 1054, 1074
`\l__slcd_packages_microtype_bool`
. 913, 946, 980, 1070
`\l__slcd_packages_minted_bool`
. 908, 929, 967, 976, 1009
`\l__slcd_packages_selnolig_bool`
. 911, 938, 978, 1041
`\l__slcd_packages_siunitx_bool`
. 907, 926, 975, 995
`\l__slcd_pagemark_minipage_dim`
. 58, 233, 249, 257, 269
`\l__slcd_paper_int` 41, 72, 190, 210
`\l__slcd_print_title:` 375, 385
`\l__slcd_rulerraise_dim` 58, 230, 246, 264, 276
`\l__slcd_rulespace_dim`
. 58, 232, 243, 248, 261, 273
`\l__slcd_rulethickness_dim`
. 58, 230, 246, 264, 276
`\l__slcd_rulewidth_dim` 58, 230, 246, 264, 276
`\l__slcd_signature_tl` . 45, 294, 295, 608, 621
`\l__slcd_supervisor_tl` . . . 45, 157, 453, 455
`\l__slcd_thesis_type_tl` 72, 401,
414, 427, 429, 431, 433, 435, 490, 492, 494
`\l__slcd_title_box` 365, 373, 379
`\l__slcd_unknown_clsopts_prop` . . 42, 72, 130
`\l__slcd_version_tl` . . 33, 36, 39, 45, 145, 479
`\smallskip` 482
`\space` 1154
`\strut` 623
`\strutbox` 308
`\subsection` 533, 550, 600
`summary (env.)` 6, 640
`\supervisor` 4, 155
sys commands:
`\sys_if_engine luatex_p:` . 9, 863, 1041, 1054
`\sys_if_engine pdftex_p:` 9, 861
`\sys_if_engine xetex_p:` 9, 862

T

`\tabcaption` 11, 13

T_EX and L^AT_EX 2_ε commands:
`\@author` 4, 290, 395, 488
`\@colht` 321, 337
`\@colroom` 322, 338
`\@date` 33, 36, 39, 480, 620
`\@empty` 359, 382, 390
`\@ifl@t@r` 5, 16
`\@ifpackagelater` 16
`\@ifpackageloaded` 16
`\@ifundefined` 2
`\@lowertitleback` 4, 28, 357, 486
`\@mainmatterfalse` 564, 576
`\@mainmattertrue` 560, 570
`\@maketitle` 3, 25, 346, 369
`\@plus` 343, 371
`\@subtitle` 390, 391
`\@tempswatrue` 349
`\@thanks` 359, 382
`\@title` 388, 489
`\@titlepageiscoverpagefalse` 324
`\@uppertitleback` 353
`\cbx@margcitewrap` 1170, 1176, 1186
`\cbx@savedcites` 1168, 1171, 1173, 1182
`\if@mainmatter` 560
`\if@tempswa` 350
`\if@twoside` 348, 563, 569, 575
`\l@lowertitleback` 4
`\next@tpage` 351
`\par@updaterelative` 343, 371
`\scr@ifundefinedorrelax` 531, 548, 598
`\titlepage@restore` 319, 325, 362
`\z@` 343, 371
`\textbf` 234, 250, 258, 270, 488
`\textemdash` 1083
`\textheight` 332, 337, 338, 339
`\textls` 516, 520
`\textwidth` 307, 309,
331, 340, 341, 352, 356, 375, 407, 420, 509
`\the` 321, 322, 323, 496
`\thechapter` 505
`\thefield` 1182
`\thefootnote` 318
`\theoremseparator` 636
`thesistype` 3
`\thispagestyle` 344, 372
`\title` 3, 20
`\titlepagestyle` 314
tl commands:
`\tl_gset:Nn` 76, 78, 90, 92, 94, 96, 98,
99, 101, 584, 731, 735, 739, 836, 839, 842, 981
`\tl_gset_eq:NN` 106
`\tl_if_empty:NTF` 201, 437, 442, 443,
449, 453, 457, 461, 465, 469, 479, 586, 857
`\tl_if_empty:nTF` 122, 134, 293

\tl_if_eq:NnTF	401, 414, 427, 429,		
	431, 433, 435, 490, 492, 494, 1087, 1115, 1119		
\tl_new:N	42, 45, 46, 47,		
	48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 831, 910		
\tl_set:Nn	145, 149, 153, 157,		
	161, 165, 169, 173, 177, 181, 185, 294, 295		
\topmargin	328		
\toprule	11		
\ttfamily	1029		
		U	
use commands:			
\use:N	24		
\usebibmacro	1145, 1162,		
	1163, 1164, 1166, 1177, 1178, 1179, 1184		
\usekomafont	388, 391, 395, 477		
		V	
\version	3, 143		
\vfill	355		
\vsize	323, 339		
		W	
widowcontrol	12		
\widowpenalty	1077		
		X	
\xappto	1182		
\xetengine	9 , 861 , 876		
		Y	
\year	496		